



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'flatpak-make-current.1'

\$ man flatpak-make-current.1

FLATPAK MAKE-CURREN(1) flatpak make-current FLATPAK MAKE-CURREN(1)

NAME

flatpak-make-current - Make a specific version of an app current

SYNOPSIS

flatpak make-current [OPTION...] APP BRANCH

DESCRIPTION

Makes a particular branch of an application current. Only the current branch of an app has its exported files (such as desktop files and icons) made visible to the host.

When a new branch is installed it will automatically be made current, so this command is often not needed.

Unless overridden with the --user or --installation options, this command changes the default system-wide installation.

OPTIONS

The following options are understood:

-h, --help

Show help options and exit.

--user

Update a per-user installation.

`--system`

Update the default system-wide installation.

`--installation=NAME`

Updates a system-wide installation specified by NAME among those defined in `/etc/flatpak/installations.d/`. Using

`--installation=default` is equivalent to using `--system`.

`--arch=ARCH`

The architecture to make current for. See `flatpak`

`--supported-arches` for architectures supported by the host.

`-v, --verbose`

Print debug information during command processing.

`--ostree-verbose`

Print OSTree debug information during command processing.

EXAMPLES

```
$ flatpak --user make-current org.gnome.gedit 3.14
```

SEE ALSO

`flatpak(1)`, `flatpak-install(1)`, `flatpak-list(1)`

`flatpak`

`FLATPAK MAKE-CURREN(1)`