



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'foomatic-getpjloptions.8'

\$ man foomatic-getpjloptions.8

FOOMATIC-GETPJLOPTIONS(8) System Manager's Manual FOOAMATIC-GETPJLOPTIONS(8)

NAME

foomatic-getpjloptions - <put a short description here>

SYNOPSIS

foomatic-getpjloptions device

foomatic-getpjloptions hostname port

DESCRIPTION

foomatic-getpjloptions Sends a set of PJI commands and reads back the PJI options and status from a printer over a network connection or device bidirectional interface such as parallel, USB, serial. printers to standard output. The output can be piped into foomatic-addpjloptions to add options to the database.

Options

device The interface to which a local printer is connected, e.g. /dev/lp0, /dev/usb/lp0, /dev/tty00, etc. For a parallel port, you must have bidirectional support enabled at the BIOS level and the parallel port driver must support the bidirectional mode. Check your parallel port BIOS settings for

EPP/bi-directional mode.

hostname Host name or IP address of a network printer (HP JetDirect, DLINK, etc.).

port Port on which your network printer listens for socket (App? socket) connections. Most common ports are 9100 (JetDirect), 10000 (DLINK). Usually you can configure the port via a configuration interface.

EXIT STATUS

foomatic-getpjloptions returns ???

AUTHOR

Manfred Wassmann <manolo@NCC-1701.B.Shuttle.de> for the foomatic project using output from the associated binary. Modified by Patrick Powell <papowell at lprng.com> to provide better support for network printers, error messages, and remove CR and FF from output.

WARNINGS

Uni-directional protocols as remote LPD are not supported as no status is returned. Some network print servers which attach to a printer parallel port do not support bidirectional mode.

Foomatic Project 2001-05-07 FOOMATIC-GETPJLOPTIONS(8)