

Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'foomatic-ppdfile.1'

\$ man foomatic-ppdfile.1

FOOMATIC-PPDFILE(1)

General Commands Manual

FOOMATIC-PPDFILE(1)

NAME

foomatic-ppdfile - Generate a PPD file for a given printer/driver combo

SYNOPSIS

foomatic-ppdfile [-w] [-d <driver>] -p <printerid>

foomatic-ppdfile [-A] [-P pattern]

foomatic-ppdfile -h

DESCRIPTION

The first form of the foomatic-ppdfile to compute the spooler-indepen? dent Foomatic PPD file for any valid printer/driver combo available in the Foomatic database, both for printing with foomatic-rip(1) and for applications/clients being able to access the printer's options. The PPD file is returned on standard ouput. If the driver is not speci? fied, the default driver is used.

The second form of the foomatic-ppdfile program will search the printer database and return either all printer entries or those whose name and/or model information match a regular expression.

The last form prints a help message and exits.

Options

-d drivername

The (optional) driver name to use. If the driver name is not sup? plied, the default or first driver in the printers compatible driver list is used.

- -p printer id The printer id.
- -w Return a PPD file that conforms to the Microsoft Windows format limitations.
- -A Return all printer entries in the database.

-Ppattern

Return all printer entries in the database which match the regular expression.

SEE ALSO

foomatic-rip(1)

EXIT STATUS

foomatic-ppdfile returns 0 on success, 1 otherwise.

AUTHOR

Manfred Wassmann <manolo@NCC-1701.B.Shuttle.de> for the foomatic project using output from the associated binary.

Modified and updated by Patrick Powell <papowell at astart.com>.

BUGS

None so far.

Please post bug reports on

http://lists.freestandards.org/mailman/listinfo/printing-foomatic

Foomatic Project 2001-05-07

FOOMATIC-PPDFILE(1)