

Full credit is given to the above companies including the OS that this PDF file was generated!

# Rocky Enterprise Linux 9.2 Manual Pages on command 'getmsg.2'

## \$ man getmsg.2

UNIMPLEMENTED(2)

Linux Programmer's Manual UNIMPLEMENTED(2)

#### NAME

afs\_syscall, break, fattach, fdetach, ftime, getmsg, getpmsg, gtty,

isastream, lock, madvise1, mpx, prof, profil, putmsg, putpmsg, secu?

rity, stty, tuxcall, ulimit, vserver - unimplemented system calls

### SYNOPSIS

Unimplemented system calls.

## DESCRIPTION

These system calls are not implemented in the Linux kernel.

### **RETURN VALUE**

These system calls always return -1 and set errno to ENOSYS.

#### NOTES

Note that ftime(3), profil(3), and ulimit(3) are implemented as library

functions.

Some system calls, like alloc\_hugepages(2), free\_hugepages(2), iop?

erm(2), iopl(2), and vm86(2) exist only on certain architectures.

Some system calls, like ipc(2), create\_module(2), init\_module(2), and

delete\_module(2) exist only when the Linux kernel was built with sup?

port for them.

## SEE ALSO

syscalls(2)

# COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

Linux 2017-09-15 UNIMPLEMENTED(2)