



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'getnetbyname\_r.3'***

***\$ man getnetbyname\_r.3***

GETNETENT\_R(3)      Linux Programmer's Manual      GETNETENT\_R(3)

NAME

getnetent\_r, getnetbyname\_r, getnetbyaddr\_r - get network entry (reen?  
trant)

SYNOPSIS

```
#include <netdb.h>

int getnetent_r(struct netent *result_buf, char *buf,
               size_t buflen, struct netent **result,
               int *h_errnop);

int getnetbyname_r(const char *name,
                  struct netent *result_buf, char *buf,
                  size_t buflen, struct netent **result,
                  int *h_errnop);

int getnetbyaddr_r(uint32_t net, int type,
                  struct netent *result_buf, char *buf,
                  size_t buflen, struct netent **result,
                  int *h_errnop);
```

getnetent\_r(), getnetbyname\_r(), getnetbyaddr\_r():

Since glibc 2.19:

`_DEFAULT_SOURCE`

Glibc 2.19 and earlier:

`_BSD_SOURCE` || `_SVID_SOURCE`

## DESCRIPTION

The `getnetent_r()`, `getnetbyname_r()`, and `getnetbyaddr_r()` functions are the reentrant equivalents of, respectively, `getnetent(3)`, `getnetbyname(3)`, and `getnetbyaddr(3)`. They differ in the way that the `netent` structure is returned, and in the function calling signature and return value. This manual page describes just the differences from the non-reentrant functions.

Instead of returning a pointer to a statically allocated `netent` structure as the function result, these functions copy the structure into the location pointed to by `result_buf`.

The `buf` array is used to store the string fields pointed to by the returned `netent` structure. (The nonreentrant functions allocate these strings in static storage.) The size of this array is specified in `buf_len`. If `buf` is too small, the call fails with the error `ERANGE`, and the caller must try again with a larger buffer. (A buffer of length 1024 bytes should be sufficient for most applications.)

If the function call successfully obtains a network record, then `*result` is set pointing to `result_buf`; otherwise, `*result` is set to `NULL`.

The buffer pointed to by `h_errnop` is used to return the value that would be stored in the global variable `h_errno` by the nonreentrant versions of these functions.

## RETURN VALUE

On success, these functions return 0. On error, they return one of the positive error numbers listed in `ERRORS`.

On error, record not found (`getnetbyname_r()`, `getnetbyaddr_r()`), or end of input (`getnetent_r()`) result is set to `NULL`.

## ERRORS

`ENOENT` (`getnetent_r()`) No more records in database.

ERANGE buf is too small. Try again with a larger buffer (and increased buflen).

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

????????????????????????????????????????????????????????????

?Interface ? Attribute ? Value ?

????????????????????????????????????????????????????????????

?getnetent\_r(), ? Thread safety ? MT-Safe locale ?

?getnetbyname\_r(), ? ? ?

?getnetbyaddr\_r() ? ? ?

????????????????????????????????????????????????????????????

## CONFORMING TO

These functions are GNU extensions. Functions with similar names exist on some other systems, though typically with different calling signatures.

## SEE ALSO

getnetent(3), networks(5)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.