



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'gtk-query-immodules-3.0.1'***

**\$ man gtk-query-immodules-3.0.1**

GTK-QUERY-IMMODULE(1)      User Commands      GTK-QUERY-IMMODULE(1)

#### **NAME**

gtk-query-immodules-3.0 - Input method module registration utility

#### **SYNOPSIS**

gtk-query-immodules-3.0 [--update-cache] [MODULE...]

#### **DESCRIPTION**

gtk-query-immodules-3.0 collects information about loadable input

method modules for GTK+ and writes it to the default cache file

location, or to stdout.

If called without arguments, it looks for modules in the GTK+ input  
method module path.

If called with arguments, it looks for the specified modules. The  
arguments may be absolute or relative paths.

Normally, the output of gtk-query-immodules-3.0 is written to  
libdir/gtk-3.0/3.0.0/immodules.cache, where GTK+ looks for it by  
default. If it is written to some other location, the  
GTK\_IM\_MODULE\_FILE environment variable can be set to point GTK+ at the  
file.

## OPTIONS

--update-cache

Write the output to the default cache location instead of stdout

## FILES

libdir/gtk-3.0/3.0.0/immodules.cache

The default im cache file used by GTK+ applications

## ENVIRONMENT

GTK\_PATH

Prepends directories to the input method module path

GTK\_IM\_MODULE\_FILE

Specifies an alternative im module cache for GTK+ applications

GTK+

GTK-QUERY-IMMODULE(1)