



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'htons.3'

\$ man htons.3

BYTEORDER(3) Linux Programmer's Manual BYTEORDER(3)

NAME

htonl, htons, ntohs, ntohl, ntohs - convert values between host and network

byte order

SYNOPSIS

```
#include <arpa/inet.h>

uint32_t htonl(uint32_t hostlong);
uint16_t htons(uint16_t hostshort);
uint32_t ntohl(uint32_t netlong);
uint16_t ntohs(uint16_t netshort);
```

DESCRIPTION

The htonl() function converts the unsigned integer hostlong from host byte order to network byte order.

The htons() function converts the unsigned short integer hostshort from host byte order to network byte order.

The ntohl() function converts the unsigned integer netlong from network byte order to host byte order.

The ntohs() function converts the unsigned short integer netshort from

network byte order to host byte order.

On the i386 the host byte order is Least Significant Byte first,
whereas the network byte order, as used on the Internet, is Most Sig?
nificant Byte first.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?htonl(), htons(), ntohs(), ntohs() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

Some systems require the inclusion of <netinet/in.h> instead of

<arpa/inet.h>.

SEE ALSO

bswap(3), endian(3), gethostbyname(3), getservent(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A
description of the project, information about reporting bugs, and the
latest version of this page, can be found at
<https://www.kernel.org/doc/man-pages/>.

GNU

2017-09-15

BYTEORDER(3)