



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'iconv\_close.3'***

**\$ man iconv\_close.3**

ICONV\_CLOSE(3)          Linux Programmer's Manual          ICONV\_CLOSE(3)

#### NAME

iconv\_close - deallocate descriptor for character set conversion

#### SYNOPSIS

```
#include <iconv.h>

int iconv_close(iconv_t cd);
```

#### DESCRIPTION

The iconv\_close() function deallocates a conversion descriptor cd previously allocated using iconv\_open(3).

#### RETURN VALUE

When successful, the iconv\_close() function returns 0. In case of error, it sets errno and returns -1.

#### VERSIONS

This function is available in glibc since version 2.1.

#### ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?iconv\_close() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SUSv2.

SEE ALSO

iconv(3), iconv\_open(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU 2017-09-15 ICONV\_CLOSE(3)