



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ioctl_ficlone.2'

\$ man ioctl_ficlone.2

IOCTL_FICLONERANGE(2) Linux Programmer's Manual IOCTL_FICLONERANGE(2)

NAME

ioctl_ficlone, ioctl_ficlone - share some the data of one file with another file

SYNOPSIS

```
#include <sys/ioctl.h>
#include <linux/fs.h>
int ioctl(int dest_fd, FICLONERANGE, struct file_clone_range *arg);
int ioctl(int dest_fd, FICLONE, int src_fd);
```

DESCRIPTION

If a filesystem supports files sharing physical storage between multiple files ("reflink"), this ioctl(2) operation can be used to make some of the data in the src_fd file appear in the dest_fd file by sharing the underlying storage, which is faster than making a separate physical copy of the data. Both files must reside within the same filesystem. If a file write should occur to a shared region, the filesystem must ensure that the changes remain private to the file being written. This behavior is commonly referred to as "copy on write".

This `ioctl` reflinks up to `src_length` bytes from file descriptor `src_fd` at offset `src_offset` into the file `dest_fd` at offset `dest_offset`, provided that both are files. If `src_length` is zero, the `ioctl` reflinks to the end of the source file. This information is conveyed in a structure of the following form:

```
struct file_clone_range {
    __s64 src_fd;
    __u64 src_offset;
    __u64 src_length;
    __u64 dest_offset;
};
```

Clones are atomic with regards to concurrent writes, so no locks need to be taken to obtain a consistent cloned copy.

The `FICLONE` `ioctl` clones entire files.

RETURN VALUE

On error, `-1` is returned, and `errno` is set to indicate the error.

ERRORS

Error codes can be one of, but are not limited to, the following:

`EBADF` `src_fd` is not open for reading; `dest_fd` is not open for writing or is open for append-only writes; or the filesystem which `src_fd` resides on does not support reflink.

`EINVAL` The filesystem does not support reflinking the ranges of the given files. This error can also appear if either file descriptor represents a device, FIFO, or socket. Disk filesystems generally require the offset and length arguments to be aligned to the fundamental block size. XFS and Btrfs do not support overlapping reflink ranges in the same file.

`EISDIR` One of the files is a directory and the filesystem does not support shared regions in directories.

EOPNOTSUPP

This can appear if the filesystem does not support reflinking either file descriptor, or if either file descriptor refers to special inodes.

EPERM dest_fd is immutable.

ETXTBSY

One of the files is a swap file. Swap files cannot share storage.

EXDEV dest_fd and src_fd are not on the same mounted filesystem.

VERSIONS

These ioctl operations first appeared in Linux 4.5. They were previously known as BTRFS_IOC_CLONE and BTRFS_IOC_CLONE_RANGE, and were private to Btrfs.

CONFORMING TO

This API is Linux-specific.

NOTES

Because a copy-on-write operation requires the allocation of new storage, the fallocate(2) operation may unshare shared blocks to guarantee that subsequent writes will not fail because of lack of disk space.

SEE ALSO

ioctl(2)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux 2017-09-15 IOCTL_FICLONERANGE(2)