



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ioprio\_get.2'***

***\$ man ioprio\_get.2***

IOPRIO\_SET(2)          Linux Programmer's Manual          IOPRIO\_SET(2)

NAME

`ioprio_get`, `ioprio_set` - get/set I/O scheduling class and priority

SYNOPSIS

`int ioprio_get(int which, int who);`

`int ioprio_set(int which, int who, int ioprio);`

Note: There are no glibc wrappers for these system calls; see NOTES.

DESCRIPTION

The `ioprio_get()` and `ioprio_set()` system calls get and set the I/O scheduling class and priority of one or more threads.

The `which` and `who` arguments identify the thread(s) on which the system calls operate. The `which` argument determines how `who` is interpreted, and has one of the following values:

**IOPRIO\_WHO\_PROCESS**

`who` is a process ID or thread ID identifying a single process or thread. If `who` is 0, then operate on the calling thread.

**IOPRIO\_WHO\_PGRP**

`who` is a process group ID identifying all the members of a

process group. If who is 0, then operate on the process group of which the caller is a member.

#### IOPRIO\_WHO\_USER

who is a user ID identifying all of the processes that have a matching real UID.

If which is specified as IOPRIO\_WHO\_PGRP or IOPRIO\_WHO\_USER when call?

ing ioprio\_get(), and more than one process matches who, then the re?

turned priority will be the highest one found among all of the matching

processes. One priority is said to be higher than another one if it

belongs to a higher priority class (IOPRIO\_CLASS\_RT is the highest pri?

ority class; IOPRIO\_CLASS\_IDLE is the lowest) or if it belongs to the

same priority class as the other process but has a higher priority

level (a lower priority number means a higher priority level).

The ioprio argument given to ioprio\_set() is a bit mask that specifies

both the scheduling class and the priority to be assigned to the target

process(es). The following macros are used for assembling and dissect?

ing ioprio values:

#### IOPRIO\_PRIO\_VALUE(class, data)

Given a scheduling class and priority (data), this macro com?

bins the two values to produce an ioprio value, which is re?

turned as the result of the macro.

#### IOPRIO\_PRIO\_CLASS(mask)

Given mask (an ioprio value), this macro returns its I/O class

component, that is, one of the values IOPRIO\_CLASS\_RT, IO?

PRIO\_CLASS\_BE, or IOPRIO\_CLASS\_IDLE.

#### IOPRIO\_PRIO\_DATA(mask)

Given mask (an ioprio value), this macro returns its priority

(data) component.

See the NOTES section for more information on scheduling classes and

priorities, as well as the meaning of specifying ioprio as 0.

I/O priorities are supported for reads and for synchronous (O\_DIRECT,

O\_SYNC) writes. I/O priorities are not supported for asynchronous

writes because they are issued outside the context of the program

dirtying the memory, and thus program-specific priorities do not apply.

## RETURN VALUE

On success, `ioprio_get()` returns the `ioprio` value of the process with highest I/O priority of any of the processes that match the criteria specified in `which` and `who`. On error, -1 is returned, and `errno` is set to indicate the error.

On success, `ioprio_set()` returns 0. On error, -1 is returned, and `errno` is set to indicate the error.

## ERRORS

**EINVAL** Invalid `value` for `which` or `ioprio`. Refer to the NOTES section for available scheduler classes and priority levels for `ioprio`.

**EPERM** The calling process does not have the privilege needed to assign this `ioprio` to the specified process(es). See the NOTES section for more information on required privileges for `ioprio_set()`.

**ESRCH** No process(es) could be found that matched the specification in `which` and `who`.

## VERSIONS

These system calls have been available on Linux since kernel 2.6.13.

## CONFORMING TO

These system calls are Linux-specific.

## NOTES

Glibc does not provide a wrapper for these system calls; call them using `syscall(2)`.

Two or more processes or threads can share an I/O context. This will be the case when `clone(2)` was called with the `CLONE_IO` flag. However, by default, the distinct threads of a process will not share the same I/O context. This means that if you want to change the I/O priority of all threads in a process, you may need to call `ioprio_set()` on each of the threads. The thread ID that you would need for this operation is the one that is returned by `gettid(2)` or `clone(2)`.

These system calls have an effect only when used in conjunction with an I/O scheduler that supports I/O priorities. As at kernel 2.6.17 the only such scheduler is the Completely Fair Queuing (CFQ) I/O scheduler.

If no I/O scheduler has been set for a thread, then by default the I/O priority will follow the CPU nice value (setpriority(2)). In Linux kernels before version 2.6.24, once an I/O priority had been set using `ioprio_set()`, there was no way to reset the I/O scheduling behavior to the default. Since Linux 2.6.24, specifying `ioprio` as 0 can be used to reset to the default I/O scheduling behavior.

### Selecting an I/O scheduler

I/O schedulers are selected on a per-device basis via the special file `/sys/block/<device>/queue/scheduler`.

One can view the current I/O scheduler via the `/sys` filesystem. For example, the following command displays a list of all schedulers currently loaded in the kernel:

```
$ cat /sys/block/sda/queue/scheduler
noop anticipatory deadline [cfq]
```

The scheduler surrounded by brackets is the one actually in use for the device (`sda` in the example). Setting another scheduler is done by writing the name of the new scheduler to this file. For example, the following command will set the scheduler for the `sda` device to `cfq`:

```
$ su
Password:
# echo cfq > /sys/block/sda/queue/scheduler
```

### The Completely Fair Queuing (CFQ) I/O scheduler

Since version 3 (also known as CFQ Time Sliced), CFQ implements I/O nice levels similar to those of CPU scheduling. These nice levels are grouped into three scheduling classes, each one containing one or more priority levels:

#### IOPRIO\_CLASS\_RT (1)

This is the real-time I/O class. This scheduling class is given higher priority than any other class: processes from this class are given first access to the disk every time. Thus, this I/O class needs to be used with some care: one I/O real-time process can starve the entire system. Within the real-time class, there are 8 levels of class data (priority) that determine exactly how

much time this process needs the disk for on each service. The highest real-time priority level is 0; the lowest is 7. In the future, this might change to be more directly mappable to performance, by passing in a desired data rate instead.

#### IOPRIO\_CLASS\_BE (2)

This is the best-effort scheduling class, which is the default for any process that hasn't set a specific I/O priority. The class data (priority) determines how much I/O bandwidth the process will get. Best-effort priority levels are analogous to CPU nice values (see `getpriority(2)`). The priority level determines a priority relative to other processes in the best-effort scheduling class. Priority levels range from 0 (highest) to 7 (lowest).

#### IOPRIO\_CLASS\_IDLE (3)

This is the idle scheduling class. Processes running at this level get I/O time only when no one else needs the disk. The idle class has no class data. Attention is required when assigning this priority class to a process, since it may become starved if higher priority processes are constantly accessing the disk.

Refer to the kernel source file `Documentation/block/ioprio.txt` for more information on the CFQ I/O Scheduler and an example program.

#### Required permissions to set I/O priorities

Permission to change a process's priority is granted or denied based on two criteria:

##### Process ownership

An unprivileged process may set the I/O priority only for a process whose real UID matches the real or effective UID of the calling process. A process which has the `CAP_SYS_NICE` capability can change the priority of any process.

##### What is the desired priority

Attempts to set very high priorities (`IOPRIO_CLASS_RT`) require the `CAP_SYS_ADMIN` capability. Kernel versions up to 2.6.24 also

required CAP\_SYS\_ADMIN to set a very low priority (IO? PRIO\_CLASS\_IDLE), but since Linux 2.6.25, this is no longer required.

A call to ioprio\_set() must follow both rules, or the call will fail with the error EPERM.

## BUGS

Glibc does not yet provide a suitable header file defining the function prototypes and macros described on this page. Suitable definitions can be found in linux/ioprio.h.

## SEE ALSO

ionice(1), getpriority(2), open(2), capabilities(7), cgroups(7)

Documentation/block/ioprio.txt in the Linux kernel source tree

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux                    2019-03-06                    IOPRIO\_SET(2)