



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ip-mptcp.8'

\$ man ip-mptcp.8

IP-MPTCP(8) Linux IP-MPTCP(8)

NAME

ip-mptcp - MPTCP path manager configuration

SYNOPSIS

ip [OPTIONS] mptcp { endpoint | limits | help }

ip mptcp endpoint add IFADDR [port PORT] [dev IFNAME] [id ID] [FLAG-LIST]

ip mptcp endpoint delete id ID [IFADDR]

ip mptcp endpoint change [id ID] [IFADDR] [port PORT] CHANGE-OPT

ip mptcp endpoint show [id ID]

ip mptcp endpoint flush

FLAG-LIST := [FLAG-LIST] FLAG

FLAG := [signal | subflow | backup | fullmesh]

CHANGE-OPT := [backup | nobackup | fullmesh | nofullmesh]

ip mptcp limits set [subflow SUBFLOW_NR] [add_addr_accepted ADD_ADDR_ACCEPTED_NR]

ip mptcp limits show

ip mptcp monitor

DESCRIPTION

MPTCP is a transport protocol built on top of TCP that allows TCP connections to use multiple paths to maximize resource usage and increase redundancy. The `ip-mptcp` sub-commands allow configuring several aspects of the MPTCP path manager, which is in charge of subflows creation:

The endpoint object specifies the IP addresses that will be used and/or announced for additional subflows:

`ip mptcp endpoint add` add new MPTCP endpoint

`ip mptcp endpoint delete` delete existing MPTCP endpoint

`ip mptcp endpoint show` get existing MPTCP endpoint

`ip mptcp endpoint flush` flush all existing MPTCP endpoints

IFADDR An IPv4 or IPv6 address. When used with the `delete id` operation,

an IFADDR is only included when the ID is 0.

PORT When a port number is specified, incoming MPTCP subflows for al?

ready established MPTCP sockets will be accepted on the speci?

fied port, regardless the original listener port accepting the

first MPTCP subflow and/or this peer being actually on the

client side.

ID is a unique numeric identifier for the given endpoint

signal The endpoint will be announced/signaled to each peer via an

MPTCP `ADD_ADDR` sub-option. Upon reception of an `ADD_ADDR` sub-op?

tion, the peer can try to create additional subflows, see

`ADD_ADDR_ACCEPTED_NR`.

subflow

If additional subflow creation is allowed by the MPTCP limits,

the MPTCP path manager will try to create an additional subflow

using this endpoint as the source address after the MPTCP con?

nection is established.

backup If this is a subflow endpoint, the subflows created using this

endpoint will have the backup flag set during the connection

process. This flag instructs the peer to only send data on a

given subflow when all non-backup subflows are unavailable. This

does not affect outgoing data, where subflow priority is deter?

mined by the backup/non-backup flag received from the peer

fullmesh

If this is a subflow endpoint and additional subflow creation is allowed by the MPTCP limits, the MPTCP path manager will try to create an additional subflow for each known peer address, using this endpoint as the source address. This will occur after the MPTCP connection is established. If the peer did not announce any additional addresses using the MPTCP ADD_ADDR sub-option, this will behave the same as a plain subflow endpoint. When the peer does announce addresses, each received ADD_ADDR sub-option will trigger creation of an additional subflow to generate a full mesh topology.

The limits object specifies the constraints for subflow creations:

`ip mptcp limits show` get current MPTCP subflow creation limits

`ip mptcp limits set` change the MPTCP subflow creation limits

SUBFLOW_NR

specifies the maximum number of additional subflows allowed for each MPTCP connection. Additional subflows can be created due to: incoming accepted ADD_ADDR sub-option, local subflow endpoints, additional subflows started by the peer.

ADD_ADDR_ACCEPTED_NR

specifies the maximum number of incoming ADD_ADDR sub-options accepted for each MPTCP connection. After receiving the specified number of ADD_ADDR sub-options, any other incoming one will be ignored for the MPTCP connection lifetime. When an ADD_ADDR sub-option is accepted and there are no local fullmesh endpoints, the MPTCP path manager will try to create a new subflow using the address in the ADD_ADDR sub-option as the destination address and a source address determined using local routing resolution. When fullmesh endpoints are available, the MPTCP path manager will try to create new subflows using each fullmesh endpoint as a source address and the peer's ADD_ADDR address as the destination. In both cases the SUBFLOW_NR limit is enforced.

monitor displays creation and deletion of MPTCP connections as well as addition or removal of remote addresses and subflows.

AUTHOR

Original Manpage by Paolo Abeni <pabeni@redhat.com>

iproute2

4 Apr 2020

IP-MPTCP(8)