



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ip-mroute.8'***

**\$ man ip-mroute.8**

IP-MROUTE(8)                      Linux                      IP-MROUTE(8)

NAME

ip-mroute - multicast routing cache management

SYNOPSIS

ip mroute show [ [ to ] PREFIX ] [ from PREFIX ] [ iif DEVICE ] [ ta? ble TABLE\_ID ]

DESCRIPTION

mroute objects are multicast routing cache entries created by a user-level mrouting daemon (f.e. pimd or mrouted ).

Due to the limitations of the current interface to the multicast routing engine, it is impossible to change mroute objects administratively, so we can only display them. This limitation will be removed in the future.

ip mroute show - list mroute cache entries

to PREFIX (default)

the prefix selecting the destination multicast addresses to

list.

iif NAME

the interface on which multicast packets are received.

from PREFIX

the prefix selecting the IP source addresses of the multicast route.

table TABLE\_ID

the table id selecting the multicast table. It can be local, main, default, all or a number.

SEE ALSO

ip(8)

AUTHOR

Original Manpage by Michail Litvak <mci@owl.openwall.com>

iproute2

13 Dec 2012

IP-MROUTE(8)