



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'iswprint.3'

\$ man iswprint.3

ISWPRINT(3) Linux Programmer's Manual ISWPRINT(3)

NAME

iswprint - test for printing wide character

SYNOPSIS

```
#include <wctype.h>

int iswprint(wint_t wc);
```

DESCRIPTION

The `iswprint()` function is the wide-character equivalent of the `isprint(3)` function. It tests whether `wc` is a wide character belonging to the wide-character class "print".

The wide-character class "print" is disjoint from the wide-character class "cntrl".

The wide-character class "print" contains the wide-character class "graph".

RETURN VALUE

The `iswprint()` function returns nonzero if `wc` is a wide character belonging to the wide-character class "print". Otherwise, it returns zero.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?iswprint() ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of iswprint() depends on the LC_CTYPE category of the current locale.

SEE ALSO

isprint(3), iswctype(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU 2015-08-08 ISWPRINT(3)