





The name of the file from which to read diagnostic commands and send them to the specified Java process. Used only with the -f option. Each command in the file must be written on a single line. Lines starting with a number sign (#) are ignored. Processing of the file ends when all lines have been read or when a line containing the stop keyword is read.

command [arguments]

The command to be sent to the specified Java process. The list of available diagnostic commands for a given process can be obtained by sending the help command to this process. Each diagnostic command has its own set of arguments. To see the description, syntax, and a list of available arguments for a command, use the name of the command as the argument for the help command.

Note: If any arguments contain spaces, you must surround them with single or double quotation marks (' or "). In addition, you must escape single or double quotation marks with a backslash (\) to prevent the operating system shell from processing quotation marks.

Alternatively, you can surround these arguments with single quotation marks and then with double quotation marks (or with double quotation marks and then with single quotation marks).

## OPTIONS

Options are mutually exclusive.

-f filename

Reads commands from the specified file. This option can be used only if you specify the process identifier or the main class as the first argument. Each command in the file must be written on a single line. Lines starting with a number sign (#) are ignored.

Processing of the file ends when all lines have been read or when a line containing the stop keyword is read.

-h

-help

Prints a help message.

-l

Prints the list of running Java processes identifiers with the main class and command-line arguments.

SEE ALSO

? [jps\(1\)](#)

JDK 8

03 March 2015

[jcmd\(1\)](#)