



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'libinput-list-devices.1'

\$ man libinput-list-devices.1

libinput-list-devices(1) libinput Manual libinput-list-devices(1)

NAME

libinput-list-devices - list local devices as recognized by libinput and default values of their configuration

SYNOPSIS

libinput list-devices [--help]

DESCRIPTION

The libinput list-devices tool creates a libinput context on the default seat "seat0" and lists all devices recognized by libinput. Each device shows available configurations the respective default configuration setting.

For options that allow more settings than "enabled/disabled", all available ones are listed. The default setting is prefixed by an asterisk (*).

This tool usually needs to be run as root to have access to the /dev/input/eventX nodes.

OPTIONS

--help Print help

NOTES

Some specific feature may still be available on a device even when no configuration is exposed, a lack of a configuration option does not necessarily mean that this feature does not work.

A device may be recognized by libinput but not handled by the X.Org libinput driver or the Wayland compositor.

An xorg.conf(5) configuration entry or Wayland compositor setting may have changed configurations on a device. The libinput list-devices tool only shows the device's default configuration, not the current configuration.

LIBINPUT

Part of the libinput(1) suite

libinput 1.19.3

libinput-list-devices(1)