



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'log10.3'

\$ man log10.3

LOG10(3) Linux Programmer's Manual LOG10(3)

NAME

log10, log10f, log10l - base-10 logarithmic function

SYNOPSIS

```
#include <math.h>
```

```
double log10(double x);
```

```
float log10f(float x);
```

```
long double log10l(long double x);
```

Link with -lm.

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

log10f(), log10l():

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

```
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
```

```
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION

These functions return the base 10 logarithm of x.

RETURN VALUE

On success, these functions return the base 10 logarithm of x.

For special cases, including where x is 0, 1, negative, infinity, or NaN, see log(3).

ERRORS

See math_error(7) for information on how to determine whether an error has occurred when calling these functions.

For a discussion of the errors that can occur for these functions, see log(3).

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

????????????????????????????????????????????????????????????????

?Interface ? Attribute ? Value ?

????????????????????????????????????????????????????????????????

?log10(), log10f(), log10l() ? Thread safety ? MT-Safe ?

????????????????????????????????????????????????????????????????

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD, C89.

SEE ALSO

cbirt(3), clog10(3), exp10(3), log(3), log2(3), sqrt(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

LOG10(3)