



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'lpc-cups.8'

\$ man lpc-cups.8

lpc(8) Apple Inc. lpc(8)

NAME

lpc - line printer control program (deprecated)

SYNOPSIS

lpc [command [parameter(s)]]

DESCRIPTION

lpc provides limited control over printer and class queues provided by CUPS. It can also be used to query the state of queues.

If no command is specified on the command-line, lpc displays a prompt and accepts commands from the standard input.

COMMANDS

The lpc program accepts a subset of commands accepted by the Berkeley

lpc program of the same name:

exit Exits the command interpreter.

help [command]

? [command]

Displays a short help message.

quit Exits the command interpreter.

status [queue]

Displays the status of one or more printer or class queues.

NOTES

This program is deprecated and will be removed in a future release of CUPS.

Since lpc is geared towards the Berkeley printing system, it is impossible to use lpc to configure printer or class queues provided by CUPS.

To configure printer or class queues you must use the lpadmin(8) command or another CUPS-compatible client with that functionality.

SEE ALSO

cancel(1), cupsaccept(8), cupsenable(8), lp(1), lpadmin(8), lpr(1), lprm(1), lpstat(1), CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright © 2007-2019 by Apple Inc.

26 April 2019

CUPS

lpc(8)