



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'lsusb.8'***

**\$ man lsusb.8**

lsusb(8)                   Linux USB Utilities                   lsusb(8)

#### NAME

lsusb - list USB devices

#### SYNOPSIS

lsusb [ options ]

#### DESCRIPTION

lsusb is a utility for displaying information about USB buses in the system and the devices connected to them.

#### OPTIONS

-v, --verbose

Tells lsusb to be verbose and display detailed information about the devices shown. This includes configuration descriptors for the device's current speed. Class descriptors will be shown, when available, for USB device classes including hub, audio,

HID, communications, and chipcard. Can be used with the `-t` option.

`-s [[bus]:][devnum]`

Show only devices in specified bus and/or devnum. Both ID's are given in decimal and may be omitted.

`-d [vendor]:[product]`

Show only devices with the specified vendor and product ID. Both ID's are given in hexadecimal.

`-D device`

Do not scan the `/dev/bus/usb` directory, instead display only information about the device whose device file is given. The device file should be something like `/dev/bus/usb/001/001`. This option displays detailed information like the `-v` option; you must be root to do this.

`-t, --tree`

Tells `lsusb` to dump the physical USB device hierarchy as a tree. Verbosity can be increased twice with `-v` option.

`-V, --version`

Print version information on standard output, then exit successfully.

## RETURN VALUE

If the specified device is not found, a non-zero exit code is returned.

## SEE ALSO

`lspci(8)`, `usbview(8)`.

Thomas Sailer, <sailer@ife.ee.ethz.ch>.

usbutils-013

11 February 2019

lsusb(8)