



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'malloc\_info.3'***

#### ***\$ man malloc\_info.3***

MALLOC\_INFO(3)      Linux Programmer's Manual      MALLOC\_INFO(3)

#### NAME

malloc\_info - export malloc state to a stream

#### SYNOPSIS

```
#include <malloc.h>
```

```
int malloc_info(int options, FILE *stream);
```

#### DESCRIPTION

The malloc\_info() function exports an XML string that describes the current state of the memory-allocation implementation in the caller.

The string is printed on the file stream stream. The exported string includes information about all arenas (see malloc(3)).

As currently implemented, options must be zero.

#### RETURN VALUE

On success, malloc\_info() returns 0; on error, it returns -1, with errno set to indicate the cause.

#### ERRORS

EINVAL options was nonzero.

#### VERSIONS

malloc\_info() was added to glibc in version 2.10.

## ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?malloc\_info() ? Thread safety ? MT-Safe ?

??

## CONFORMING TO

This function is a GNU extension.

## NOTES

The memory-allocation information is provided as an XML string (rather than a C structure) because the information may change over time (according to changes in the underlying implementation). The output XML string includes a version field.

The open\_memstream(3) function can be used to send the output of malloc\_info() directly into a buffer in memory, rather than to a file.

The malloc\_info() function is designed to address deficiencies in malloc\_stats(3) and mallinfo(3).

## EXAMPLES

The program below takes up to four command-line arguments, of which the first three are mandatory. The first argument specifies the number of threads that the program should create. All of the threads, including the main thread, allocate the number of blocks of memory specified by the second argument. The third argument controls the size of the blocks to be allocated. The main thread creates blocks of this size, the second thread created by the program allocates blocks of twice this size, the third thread allocates blocks of three times this size, and so on.

The program calls malloc\_info() twice to display the memory-allocation state. The first call takes place before any threads are created or memory allocated. The second call is performed after all threads have

allocated memory.

In the following example, the command-line arguments specify the creation of one additional thread, and both the main thread and the additional thread allocate 10000 blocks of memory. After the blocks of memory have been allocated, malloc\_info() shows the state of two allocation arenas.

```
$ getconf GNU_LIBC_VERSION
```

```
glibc 2.13
```

```
$ ./a.out 1 10000 100
```

```
===== Before allocating blocks =====
```

```
<malloc version="1">
```

```
<heap nr="0">
```

```
<sizes>
```

```
</sizes>
```

```
<total type="fast" count="0" size="0"/>
```

```
<total type="rest" count="0" size="0"/>
```

```
<system type="current" size="135168"/>
```

```
<system type="max" size="135168"/>
```

```
<aspace type="total" size="135168"/>
```

```
<aspace type="mprotect" size="135168"/>
```

```
</heap>
```

```
<total type="fast" count="0" size="0"/>
```

```
<total type="rest" count="0" size="0"/>
```

```
<system type="current" size="135168"/>
```

```
<system type="max" size="135168"/>
```

```
<aspace type="total" size="135168"/>
```

```
<aspace type="mprotect" size="135168"/>
```

```
</malloc>
```

```
===== After allocating blocks =====
```

```
<malloc version="1">
```

```
<heap nr="0">
```

```
<sizes>
```

```
</sizes>
```

```

<total type="fast" count="0" size="0"/>
<total type="rest" count="0" size="0"/>
<system type="current" size="1081344"/>
<system type="max" size="1081344"/>
<aspace type="total" size="1081344"/>
<aspace type="mprotect" size="1081344"/>
</heap>
<heap nr="1">
<sizes>
</sizes>
<total type="fast" count="0" size="0"/>
<total type="rest" count="0" size="0"/>
<system type="current" size="1032192"/>
<system type="max" size="1032192"/>
<aspace type="total" size="1032192"/>
<aspace type="mprotect" size="1032192"/>
</heap>
<total type="fast" count="0" size="0"/>
<total type="rest" count="0" size="0"/>
<system type="current" size="2113536"/>
<system type="max" size="2113536"/>
<aspace type="total" size="2113536"/>
<aspace type="mprotect" size="2113536"/>
</malloc>

```

#### Program source

```

#include <unistd.h>
#include <stdlib.h>
#include <pthread.h>
#include <malloc.h>
#include <errno.h>
static size_t blockSize;
static int numThreads, numBlocks;
#define errExit(msg) do { perror(msg); exit(EXIT_FAILURE); \

```

```

        } while (0)

static void *
thread_func(void *arg)
{
    int tn = (int) arg;

    /* The multiplier '(2 + tn)' ensures that each thread (including
       the main thread) allocates a different amount of memory */
    for (int j = 0; j < numBlocks; j++)
        if (malloc(blockSize * (2 + tn)) == NULL)
            errExit("malloc-thread");

    sleep(100);    /* Sleep until main thread terminates */
    return NULL;
}

int
main(int argc, char *argv[])
{
    int sleepTime;

    if (argc < 4) {
        fprintf(stderr,
                "%s num-threads num-blocks block-size [sleep-time]\n",
                argv[0]);
        exit(EXIT_FAILURE);
    }

    numThreads = atoi(argv[1]);
    numBlocks = atoi(argv[2]);
    blockSize = atoi(argv[3]);
    sleepTime = (argc > 4) ? atoi(argv[4]) : 0;

    pthread_t *thr = calloc(numThreads, sizeof(*thr));
    if (thr == NULL)
        errExit("calloc");

    printf("===== Before allocating blocks =====\n");
    malloc_info(0, stdout);

    /* Create threads that allocate different amounts of memory */

```

```

for (int tn = 0; tn < numThreads; tn++) {
    errno = pthread_create(&thr[tn], NULL, thread_func,
                          (void *) tn);
    if (errno != 0)
        errExit("pthread_create");
    /* If we add a sleep interval after the start-up of each
       thread, the threads likely won't contend for malloc
       mutexes, and therefore additional arenas won't be
       allocated (see malloc(3)). */
    if (sleepTime > 0)
        sleep(sleepTime);
}
/* The main thread also allocates some memory */
for (int j = 0; j < numBlocks; j++)
    if (malloc(blockSize) == NULL)
        errExit("malloc");
sleep(2);    /* Give all threads a chance to
              complete allocations */
printf("\n===== After allocating blocks =====\n");
malloc_info(0, stdout);
exit(EXIT_SUCCESS);
}

```

#### SEE ALSO

mallinfo(3), malloc(3), malloc\_stats(3), mallopt(3), open\_memstream(3)

#### COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.