



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'mblen.3'

\$ man mblen.3

MBLEN(3) Linux Programmer's Manual MBLEN(3)

NAME

mblen - determine number of bytes in next multibyte character

SYNOPSIS

```
#include <stdlib.h>
```

```
int mblen(const char *s, size_t n);
```

DESCRIPTION

If `s` is not NULL, the `mblen()` function inspects at most `n` bytes of the multibyte string starting at `s` and extracts the next complete multibyte character. It uses a static anonymous shift state known only to the `mblen()` function. If the multibyte character is not the null wide character, it returns the number of bytes that were consumed from `s`.

If the multibyte character is the null wide character, it returns 0.

If the `n` bytes starting at `s` do not contain a complete multibyte character, `mblen()` returns -1. This can happen even if `n` is greater than or equal to `MB_CUR_MAX`, if the multibyte string contains redundant shift sequences.

If the multibyte string starting at `s` contains an invalid multibyte se?

quence before the next complete character, `mblen()` also returns -1. If `s` is NULL, the `mblen()` function resets the shift state, known to only this function, to the initial state, and returns nonzero if the encoding has nontrivial shift state, or zero if the encoding is stateless.

RETURN VALUE

The `mblen()` function returns the number of bytes parsed from the multibyte sequence starting at `s`, if a non-null wide character was recognized. It returns 0, if a null wide character was recognized. It returns -1, if an invalid multibyte sequence was encountered or if it couldn't parse a complete multibyte character.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

??

?Interface ? Attribute ? Value ?

??

?`mblen()` ? Thread safety ? MT-Unsafe race ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of `mblen()` depends on the `LC_CTYPE` category of the current locale.

The function `mbrlen(3)` provides a better interface to the same functionality.

SEE ALSO

`mbrlen(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

