



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'mecab.1'

\$ man mecab.1

MECAB(1) MeCab MECAB(1)

NAME

mecab - manual page for mecab of 0.98pre1

SYNOPSIS

mecab [options] files

DESCRIPTION

MeCab: Yet Another Part-of-Speech and Morphological Analyzer

Copyright(C) 2001-2008 Taku Kudo Copyright(C) 2004-2008 Nippon Tele?

graph and Telephone Corporation

-r, --rcfile=FILE

use FILE as resource file

-d, --dicdir=DIR

set DIR as a system dicdir

-u, --userdic=FILE

use FILE as a user dictionary

-l, --lattice-level=INT

lattice information level (default 0)

-D, --dictionary-info

show dictionary information and exit

-a, --all-morphs
 output all morphs(default false)

-O, --output-format-type=TYPE
 set output format type (wakati,none,...)

-p, --partial
 partial parsing mode

-F, --node-format=STR
 use STR as the user-defined node format

-U, --unk-format=STR
 use STR as the user-defined unk format

-B, --bos-format=STR
 use STR as the user-defined bos format

-E, --eos-format=STR
 use STR as the user-defined eos format

-x, --unk-feature=STR
 use STR as the feature for unknown word

-b, --input-buffer-size=INT
 set input buffer size (default 8192)

-P, --dump-config
 dump MeCab parameters

-M, --open-mutable-dictionary
 open dictioanry with mutable mode (experimental)

-C, --allocate-sentence
 allocate new memory for input sentence

-N, --nbest=INT
 output N best results (default 1)

-t, --theta=FLOAT
 set temparature parameter theta (default 0.75)

-c, --cost-factor=INT
 set cost factor (default 700)

-o, --output=FILE
 set the output file name

-v, --version

show the version and exit.

-h, --help

show this help and exit.

mecab of 0.98pre1

March 2009

MECAB(1)