



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'msgunfmt.1'***

**\$ man msgunfmt.1**

MSGUNFMT(1) User Commands MSGUNFMT(1)

NAME

msgunfmt - uncompile message catalog from binary format

SYNOPSIS

msgunfmt [OPTION] [FILE]...

DESCRIPTION

Convert binary message catalog to Uniform style .po file.

Mandatory arguments to long options are mandatory for short options too.

Operation mode:

-j, --java

Java mode: input is a Java ResourceBundle class

--csharp

C# mode: input is a .NET .dll file

--csharp-resources

C# resources mode: input is a .NET .resources file

--tcl Tcl mode: input is a tcl/msgcat .msg file

Input file location:

FILE ...

input .mo files

If no input file is given or if it is -, standard input is read.

Input file location in Java mode:

-r, --resource=RESOURCE

resource name

-l, --locale=LOCALE

locale name, either language or language\_COUNTRY

The class name is determined by appending the locale name to the resource name, separated with an underscore. The class is located using the CLASSPATH.

Input file location in C# mode:

-r, --resource=RESOURCE

resource name

-l, --locale=LOCALE

locale name, either language or language\_COUNTRY

-d DIRECTORY

base directory for locale dependent .dll files

The -l and -d options are mandatory. The .dll file is located in a subdirectory of the specified directory whose name depends on the locale.

Input file location in Tcl mode:

-l, --locale=LOCALE

locale name, either language or language\_COUNTRY

-d DIRECTORY

base directory of .msg message catalogs

The -l and -d options are mandatory. The .msg file is located in the specified directory.

Output file location:

-o, --output-file=FILE

write output to specified file

The results are written to standard output if no output file is specified or if it is -.

## Output details:

--color

use colors and other text attributes always

--color=WHEN

use colors and other text attributes if WHEN. WHEN may be 'always', 'never', 'auto', or 'html'.

--style=STYLEFILE

specify CSS style rule file for --color

-e, --no-escape

do not use C escapes in output (default)

-E, --escape

use C escapes in output, no extended chars

--force-po

write PO file even if empty

-i, --indent

write indented output style

--strict

write strict uniform style

-p, --properties-output

write out a Java .properties file

--stringtable-output

write out a NeXTstep/GNUstep .strings file

-w, --width=NUMBER

set output page width

--no-wrap

do not break long message lines, longer than the output page width, into several lines

-s, --sort-output

generate sorted output

## Informative output:

-h, --help

display this help and exit

-V, --version

output version information and exit

-v, --verbose

increase verbosity level

## AUTHOR

Written by Ulrich Drepper.

## REPORTING BUGS

Report bugs in the bug tracker at <https://savannah.gnu.org/projects/gettext> or by email to [bug-gettext@gnu.org](mailto:bug-gettext@gnu.org).

## COPYRIGHT

Copyright ? 1995-2020 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later <https://gnu.org/licenses/gpl.html>

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

## SEE ALSO

The full documentation for msgunfmt is maintained as a Texinfo manual.

If the info and msgunfmt programs are properly installed at your site,

the command

info msgunfmt

should give you access to the complete manual.

GNU gettext-tools 20200704

July 2020

MSGUNFMT(1)