



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'msguniq.1'

\$ man msguniq.1

MSGUNIQ(1) User Commands MSGUNIQ(1)

NAME

msguniq - unify duplicate translations in message catalog

SYNOPSIS

msguniq [OPTION] [INPUTFILE]

DESCRIPTION

Unifies duplicate translations in a translation catalog. Finds duplicate translations of the same message ID. Such duplicates are invalid input for other programs like msgfmt, msgmerge or msgcat. By default, duplicates are merged together. When using the --repeated option, only duplicates are output, and all other messages are discarded. Comments and extracted comments will be cumulated, except that if --use-first is specified, they will be taken from the first translation. File positions will be cumulated. When using the --unique option, duplicates are discarded.

Mandatory arguments to long options are mandatory for short options too.

Input file location:

INPUTFILE

input PO file

`-D, --directory=DIRECTORY`

add DIRECTORY to list for input files search

If no input file is given or if it is -, standard input is read.

Output file location:

`-o, --output-file=FILE`

write output to specified file

The results are written to standard output if no output file is specified or if it is -.

Message selection:

`-d, --repeated`

print only duplicates

`-u, --unique`

print only unique messages, discard duplicates

Input file syntax:

`-P, --properties-input`

input file is in Java .properties syntax

`--stringtable-input`

input file is in NeXTstep/GNUstep .strings syntax

Output details:

`-t, --to-code=NAME`

encoding for output

`--use-first`

use first available translation for each message, don't merge several translations

`--color`

use colors and other text attributes always

`--color=WHEN`

use colors and other text attributes if WHEN. WHEN may be 'always', 'never', 'auto', or 'html'.

`--style=STYLEFILE`

specify CSS style rule file for --color

-e, --no-escape

do not use C escapes in output (default)

-E, --escape

use C escapes in output, no extended chars

--force-po

write PO file even if empty

-i, --indent

write the .po file using indented style

--no-location

do not write '#: filename:line' lines

-n, --add-location

generate '#: filename:line' lines (default)

--strict

write out strict Uniform conforming .po file

-p, --properties-output

write out a Java .properties file

--stringtable-output

write out a NeXTstep/GNUstep .strings file

-w, --width=NUMBER

set output page width

--no-wrap

do not break long message lines, longer than the output page width, into several lines

-s, --sort-output

generate sorted output

-F, --sort-by-file

sort output by file location

Informative output:

-h, --help

display this help and exit

-V, --version

output version information and exit

Written by Bruno Haible.

REPORTING BUGS

Report bugs in the bug tracker at <https://savannah.gnu.org/projects/gettext> or by email to bug-gettext@gnu.org.

COPYRIGHT

Copyright ? 2001-2020 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later <https://gnu.org/licenses/gpl.html>

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for msguniqu is maintained as a Texinfo manual.

If the info and msguniqu programs are properly installed at your site,

the command

```
info msguniqu
```

should give you access to the complete manual.

GNU gettext-tools 20200704

July 2020

MSGUNIQ(1)