



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'my\_print\_defaults.1'***

***\$ man my\_print\_defaults.1***

MY\_PRINT\_DEFAULTS(1) MySQL Database System MY\_PRINT\_DEFAULTS(1)

NAME

my\_print\_defaults - display options from option files

SYNOPSIS

my\_print\_defaults [options] option\_group ...

DESCRIPTION

my\_print\_defaults displays the options that are present in option groups of option files. The output indicates what options are used by programs that read the specified option groups. For example, the mysqlcheck program reads the [mysqlcheck] and [client] option groups. To see what options are present in those groups in the standard option files, invoke my\_print\_defaults like this:

```
$> my_print_defaults mysqlcheck client
--user=myusername
--password=password
--host=localhost
```

The output consists of options, one per line, in the form that they would be specified on the command line.

my\_print\_defaults supports the following options.

? --help, -? Display a help message and exit.

? --config-file=file\_name, --defaults-file=file\_name, -c file\_name

Read only the given option file.

? --debug=debug\_options, -# debug\_options Write a debugging log. A

typical debug\_options string is d:t:o,file\_name. The default is

d:t:o,/tmp/my\_print\_defaults.trace.

? --defaults-extra-file=file\_name, --extra-file=file\_name, -e

file\_name Read this option file after the global option file but

(on Unix) before the user option file.

For additional information about this and other option-file

options, see Section 4.2.2.3, ?Command-Line Options that Affect

Option-File Handling?.

? --defaults-group-suffix=suffix, -g suffix In addition to the groups

named on the command line, read groups that have the given suffix.

For additional information about this and other option-file

options, see Section 4.2.2.3, ?Command-Line Options that Affect

Option-File Handling?.

? --login-path=name, -l name Read options from the named login path

in the .mylogin.cnf login path file. A ?login path? is an option

group containing options that specify which MySQL server to connect

to and which account to authenticate as. To create or modify a

login path file, use the mysql\_config\_editor utility. See

mysql\_config\_editor(1).

For additional information about this and other option-file

options, see Section 4.2.2.3, ?Command-Line Options that Affect

Option-File Handling?.

? --no-defaults, -n Return an empty string.

For additional information about this and other option-file

options, see Section 4.2.2.3, ?Command-Line Options that Affect

Option-File Handling?.

? --show, -s my\_print\_defaults masks passwords by default. Use this

option to display passwords as cleartext.

? --verbose, -v Verbose mode. Print more information about what the program does.

? --version, -V Display version information and exit.

## COPYRIGHT

Copyright ? 1997, 2023, Oracle and/or its affiliates.

This documentation is free software; you can redistribute it and/or modify it only under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 of the License.

This documentation is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with the program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA or see <http://www.gnu.org/licenses/>.

## SEE ALSO

For more information, please refer to the MySQL Reference Manual, which may already be installed locally and which is also available online at <http://dev.mysql.com/doc/>.

## AUTHOR

Oracle Corporation (<http://dev.mysql.com/>).

MySQL 8.0

06/02/2023

MY\_PRINT\_DEFAULTS(1)