



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'newgidmap.1'

\$ man newgidmap.1

NEWGIDMAP(1) User Commands NEWGIDMAP(1)

NAME

newgidmap - set the gid mapping of a user namespace

SYNOPSIS

newgidmap pid gid lowergid count [gid lowergid count [...]]

DESCRIPTION

The newgidmap sets /proc/[pid]/gid_map based on its command line arguments and the gids allowed. Subgid delegation can either be managed via /etc/subgid or through the configured NSS subgid module. These options are mutually exclusive.

Note that the root group is not exempted from the requirement for a valid /etc/subgid entry.

After the pid argument, newgidmap expects sets of 3 integers:

gid

Beginning of the range of GIDs inside the user namespace.

lowergid

Beginning of the range of GIDs outside the user namespace.

count

Length of the ranges (both inside and outside the user namespace).
newgidmap verifies that the caller is the owner of the process indicated by pid and that for each of the above sets, each of the GIDs in the range [lowergid, lowergid+count) is allowed to the caller according to /etc/subgid before setting /proc/[pid]/gid_map.

Note that newgidmap may be used only once for a given process.

OPTIONS

There currently are no options to the newgidmap command.

FILES

/etc/subgid

List of user's subordinate group IDs.

/proc/[pid]/gid_map

Mapping of gids from one between user namespaces.

SEE ALSO

login.defs(5), newusers(8), subgid(5), useradd(8), userdel(8),
usermod(8).

shadow-utils 4.9

09/28/2022

NEWGIDMAP(1)