



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'nologin.8'

\$ man nologin.8

NOLOGIN(8) System Administration NOLOGIN(8)

NAME

nologin - politely refuse a login

SYNOPSIS

nologin [-V] [-h]

DESCRIPTION

nologin displays a message that an account is not available and exits

non-zero. It is intended as a replacement shell field to deny login

access to an account.

If the file /etc/nologin.txt exists, nologin displays its contents to

the user instead of the default message.

The exit status returned by nologin is always 1.

OPTIONS

-c, --command command

--init-file

-i --interactive

--init-file file

-i, --interactive

-l, --login
--noprofile
--norc
--posix
--rcfile file
-r, --restricted

These shell command-line options are ignored to avoid nologin error.

-h, --help
Display help text and exit.

-V, --version
Display version information and exit.

NOTES

nologin is a per-account way to disable login (usually used for system accounts like http or ftp). nologin uses /etc/nologin.txt as an optional source for a non-default message, the login access is always refused independently of the file.

pam_nologin(8) PAM module usually prevents all non-root users from logging into the system. pam_nologin(8) functionality is controlled by /var/run/nologin or the /etc/nologin file.

HISTORY

The nologin command appeared in 4.4BSD.

AUTHORS

Karel Zak <kzak@redhat.com>

SEE ALSO

login(1), passwd(5), pam_nologin(8)

REPORTING BUGS

For bug reports, use the issue tracker at
<https://github.com/karelzak/util-linux/issues>.

AVAILABILITY

The nologin command is part of the util-linux package which can be downloaded from Linux Kernel Archive
<<https://www.kernel.org/pub/linux/utils/util-linux/>>.