



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'null.4'

\$ man null.4

NULL(4) Linux Programmer's Manual NULL(4)

NAME

null, zero - data sink

DESCRIPTION

Data written to the /dev/null and /dev/zero special files is discarded.

Reads from /dev/null always return end of file (i.e., read(2) returns

0), whereas reads from /dev/zero always return bytes containing zero

(' ' characters).

These devices are typically created by:

```
mknod -m 666 /dev/null c 1 3
```

```
mknod -m 666 /dev/zero c 1 5
```

```
chown root:root /dev/null /dev/zero
```

FILES

/dev/null

/dev/zero

NOTES

If these devices are not writable and readable for all users, many pro?

grams will act strangely.

Since Linux 2.6.31, reads from /dev/zero are interruptible by signals.

(This change was made to help with bad latencies for large reads from /dev/zero.)

SEE ALSO

chown(1), mknod(1), full(4)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2015-07-23

NULL(4)