



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ostree-diff.1'***

**\$ man ostree-diff.1**

OSTREE DIFF(1)                    ostree diff                    OSTREE DIFF(1)

#### NAME

ostree-diff - Compare a directory against a revision

#### SYNOPSIS

ostree diff [OPTIONS...] {REV\_OR\_DIR} {REV\_OR\_DIR}

#### DESCRIPTION

Compare a directory or revision against another directory or revision.

If REV\_OR\_DIR starts with ``/`` or ``.``, it is interpreted as a directory, otherwise a revision. Shows files and directories modified, added, and deleted. If there is a file in the second REV\_OR\_DIR not in the first, it will show with an "A" for "added". If a file in the first REV\_OR\_DIR is not in the second, it shows "D" for "deleted". "M" for "modified" will also show.

#### OPTIONS

--stats

Print various statistics.

--fs-diff

Print filesystem diff.

--owner-uid

Use file ownership user id for local files.

--owner-gid

Use file ownership group id for local files.

#### EXAMPLE

```
$ ostree diff my-branch^ my-branch
```

```
A /testdirectory
```

```
M /helloworld.txt
```

```
$ ostree diff my-branch my-branch^
```

```
D /testdirectory
```

```
M /helloworld.txt
```

OSTree

OSTREE DIFF(1)