



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pam.d.5'

\$ man pam.d.5

PAM.CONF(5) Linux-PAM Manual PAM.CONF(5)

NAME

pam.conf, pam.d - PAM configuration files

DESCRIPTION

When a PAM aware privilege granting application is started, it activates its attachment to the PAM-API. This activation performs a number of tasks, the most important being the reading of the configuration file(s): /etc/pam.conf. Alternatively, this may be the contents of the /etc/pam.d/ directory. The presence of this directory will cause Linux-PAM to ignore /etc/pam.conf.

These files list the PAMs that will do the authentication tasks required by this service, and the appropriate behavior of the PAM-API in the event that individual PAMs fail.

The syntax of the /etc/pam.conf configuration file is as follows. The file is made up of a list of rules, each rule is typically placed on a single line, but may be extended with an escaped end of line: `\

The format of each rule is a space separated collection of tokens, the first three being case-insensitive:

```
service type control module-path module-arguments
```

The syntax of files contained in the `/etc/pam.d/` directory, are identical except for the absence of any service field. In this case, the service is the name of the file in the `/etc/pam.d/` directory. This filename must be in lower case.

An important feature of PAM, is that a number of rules may be stacked to combine the services of a number of PAMs for a given authentication task.

The service is typically the familiar name of the corresponding application: `login` and `su` are good examples. The `service-name`, other, is reserved for giving default rules. Only lines that mention the current service (or in the absence of such, the `other` entries) will be associated with the given service-application.

The type is the management group that the rule corresponds to. It is used to specify which of the management groups the subsequent module is to be associated with. Valid entries are:

`account`

this module type performs non-authentication based account management. It is typically used to restrict/permit access to a service based on the time of day, currently available system resources (maximum number of users) or perhaps the location of the applicant user -- `'root'` login only on the console.

`auth`

this module type provides two aspects of authenticating the user.

Firstly, it establishes that the user is who they claim to be, by instructing the application to prompt the user for a password or other means of identification. Secondly, the module can grant group membership or other privileges through its credential granting properties.

`password`

this module type is required for updating the authentication token

associated with the user. Typically, there is one module for each 'challenge/response' based authentication (auth) type.

session

this module type is associated with doing things that need to be done for the user before/after they can be given service. Such things include the logging of information concerning the opening/closing of some data exchange with a user, mounting directories, etc.

If the type value from the list above is prepended with a - character the PAM library will not log to the system log if it is not possible to load the module because it is missing in the system. This can be useful especially for modules which are not always installed on the system and are not required for correct authentication and authorization of the login session.

The third field, control, indicates the behavior of the PAM-API should the module fail to succeed in its authentication task. There are two types of syntax for this control field: the simple one has a single simple keyword; the more complicated one involves a square-bracketed selection of value=action pairs.

For the simple (historical) syntax valid control values are:

required

failure of such a PAM will ultimately lead to the PAM-API returning failure but only after the remaining stacked modules (for this service and type) have been invoked.

requisite

like required, however, in the case that such a module returns a failure, control is directly returned to the application or to the superior PAM stack. The return value is that associated with the first required or requisite module to fail. Note, this flag can be used to protect against the possibility of a user getting the opportunity to enter a password over an unsafe medium. It is conceivable that such behavior might inform an attacker of valid accounts on a system. This possibility should be weighed against

the not insignificant concerns of exposing a sensitive password in a hostile environment.

sufficient

if such a module succeeds and no prior required module has failed the PAM framework returns success to the application or to the superior PAM stack immediately without calling any further modules in the stack. A failure of a sufficient module is ignored and processing of the PAM module stack continues unaffected.

optional

the success or failure of this module is only important if it is the only module in the stack associated with this service+type.

include

include all lines of given type from the configuration file specified as an argument to this control.

substack

include all lines of given type from the configuration file specified as an argument to this control. This differs from include in that evaluation of the done and die actions in a substack does not cause skipping the rest of the complete module stack, but only of the substack. Jumps in a substack also can not make evaluation jump out of it, and the whole substack is counted as one module when the jump is done in a parent stack. The reset action will reset the state of a module stack to the state it was in as of beginning of the substack evaluation.

For the more complicated syntax valid control values have the following form:

```
[value1=action1 value2=action2 ...]
```

Where valueN corresponds to the return code from the function invoked in the module for which the line is defined. It is selected from one of these: success, open_err, symbol_err, service_err, system_err, buf_err, perm_denied, auth_err, cred_insufficient, authinfo_unavail, user_unknown, maxtries, new_authtok_reqd, acct_expired, session_err, cred_unavail, cred_expired, cred_err, no_module_data, conv_err,

authtok_err, authtok_recover_err, authtok_lock_busy,
authtok_disable_aging, try_again, ignore, abort, authtok_expired,
module_unknown, bad_item, conv_again, incomplete, and default.

The last of these, default, implies 'all valueN's not mentioned explicitly. Note, the full list of PAM errors is available in /usr/include/security/_pam_types.h. The actionN can take one of the following forms:

ignore

when used with a stack of modules, the module's return status will not contribute to the return code the application obtains.

bad

this action indicates that the return code should be thought of as indicative of the module failing. If this module is the first in the stack to fail, its status value will be used for that of the whole stack.

die

equivalent to bad with the side effect of terminating the module stack and PAM immediately returning to the application.

ok

this tells PAM that the administrator thinks this return code should contribute directly to the return code of the full stack of modules. In other words, if the former state of the stack would lead to a return of PAM_SUCCESS, the module's return code will override this value. Note, if the former state of the stack holds some value that is indicative of a modules failure, this 'ok' value will not be used to override that value.

done

equivalent to ok with the side effect of terminating the module stack and PAM immediately returning to the application.

N (an unsigned integer)

jump over the next N modules in the stack. Note that N equal to 0 is not allowed, it would be treated as ignore in such case. The side effect depends on the PAM function call: for pam_authenticate,

pam_acct_mgmt, pam_chauthtok, and pam_open_session it is ignore;
for pam_setcred and pam_close_session it is one of ignore, ok, or
bad depending on the module's return value.

reset

clear all memory of the state of the module stack and start again
with the next stacked module.

Each of the four keywords: required; requisite; sufficient; and
optional, have an equivalent expression in terms of the [...] syntax.

They are as follows:

required

```
[success=ok new_authtok_reqd=ok ignore=ignore default=bad]
```

requisite

```
[success=ok new_authtok_reqd=ok ignore=ignore default=die]
```

sufficient

```
[success=done new_authtok_reqd=done default=ignore]
```

optional

```
[success=ok new_authtok_reqd=ok default=ignore]
```

module-path is either the full filename of the PAM to be used by the
application (it begins with a '/'), or a relative pathname from the
default module location: /lib/security/ or /lib64/security/, depending
on the architecture.

module-arguments are a space separated list of tokens that can be used
to modify the specific behavior of the given PAM. Such arguments will
be documented for each individual module. Note, if you wish to include
spaces in an argument, you should surround that argument with square
brackets.

```
squid auth required pam_mysql.so user=passwd_query passwd=mada \  
db=eminence [query=select user_name from internet_service \  
where user_name='%u' and password=PASSWORD('%p') and \  
service='web_proxy']
```

When using this convention, you can include '[' characters inside the
string, and if you wish to include a ']' character inside the string
that will survive the argument parsing, you should use '\]'. In other

words:

```
[.[.\].] --> ..[.].
```

Any line in (one of) the configuration file(s), that is not formatted correctly, will generally tend (erring on the side of caution) to make the authentication process fail. A corresponding error is written to the system log files with a call to `syslog(3)`.

More flexible than the single configuration file is it to configure `libpam` via the contents of the `/etc/pam.d/` directory. In this case the directory is filled with files each of which has a filename equal to a service-name (in lower-case): it is the personal configuration file for the named service.

The syntax of each file in `/etc/pam.d/` is similar to that of the `/etc/pam.conf` file and is made up of lines of the following form:

```
type control module-path module-arguments
```

The only difference being that the service-name is not present. The service-name is of course the name of the given configuration file. For example, `/etc/pam.d/login` contains the configuration for the login service.

SEE ALSO

`pam(3)`, `PAM(8)`, `pam_start(3)`

Linux-PAM Manual

11/25/2020

PAM.CONF(5)