



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pam_faildelay.8'

\$ man pam_faildelay.8

PAM_FAILDELAY(8) Linux-PAM Manual PAM_FAILDELAY(8)

NAME

pam_faildelay - Change the delay on failure per-application

SYNOPSIS

pam_faildelay.so [debug] [delay=microseconds]

DESCRIPTION

pam_faildelay is a PAM module that can be used to set the delay on failure per-application.

If no delay is given, pam_faildelay will use the value of FAIL_DELAY from /etc/login.defs.

OPTIONS

debug

Turns on debugging messages sent to syslog.

delay=N

Set the delay on failure to N microseconds.

MODULE TYPES PROVIDED

Only the auth module type is provided.

RETURN VALUES

PAM_IGNORE

Delay was successful adjusted.

PAM_SYSTEM_ERR

The specified delay was not valid.

EXAMPLES

The following example will set the delay on failure to 10 seconds:

```
auth optional pam_faildelay.so delay=10000000
```

SEE ALSO

pam_fail_delay(3), pam.conf(5), pam.d(5), pam(8)

AUTHOR

pam_faildelay was written by Darren Tucker <dtucker@zip.com.au>.