



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pam_issue.8'

\$ man pam_issue.8

PAM_ISSUE(8) Linux-PAM Manual PAM_ISSUE(8)

NAME

pam_issue - PAM module to add issue file to user prompt

SYNOPSIS

pam_issue.so [noesc] [issue=issue-file-name]

DESCRIPTION

pam_issue is a PAM module to prepend an issue file to the username prompt. It also by default parses escape codes in the issue file similar to some common getty's (using \x format).

Recognized escapes:

\d
current day

\l

name of this tty

\m

machine architecture (uname -m)

\n

machine's network node hostname (uname -n)

\o

domain name of this system

\r

release number of operating system (uname -r)

\t

current time

\s

operating system name (uname -s)

\u

number of users currently logged in

\U

same as \u except it is suffixed with "user" or "users" (eg. "1 user" or "10 users")

\v

operating system version and build date (uname -v)

OPTIONS

noesc

Turns off escape code parsing.

issue=issue-file-name

The file to output if not using the default.

MODULE TYPES PROVIDED

Only the auth module type is provided.

RETURN VALUES

PAM_BUF_ERR

Memory buffer error.

PAM_IGNORE

The prompt was already changed.

PAM_SERVICE_ERR

A service module error occurred.

PAM_SUCCESS

The new prompt was set successfully.

EXAMPLES

Add the following line to `/etc/pam.d/login` to set the user specific issue at login:

```
auth optional pam_issue.so issue=/etc/issue
```

SEE ALSO

`pam.conf(5)`, `pam.d(5)`, `pam(8)`

AUTHOR

`pam_issue` was written by Ben Collins <bcollins@debian.org>.

