



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pam_mail.8'

\$ man pam_mail.8

PAM_MAIL(8) Linux-PAM Manual PAM_MAIL(8)

NAME

pam_mail - Inform about available mail

SYNOPSIS

pam_mail.so [close] [debug] [dir=maildir] [empty] [hash=count] [noenv]
 [nopen] [quiet] [standard]

DESCRIPTION

The pam_mail PAM module provides the "you have new mail" service to the user. It can be plugged into any application that has credential or session hooks. It gives a single message indicating the newness of any mail it finds in the user's mail folder. This module also sets the PAM environment variable, MAIL, to the user's mail directory.

If the mail spool file (be it /var/mail/\$USER or a pathname given with the dir= parameter) is a directory then pam_mail assumes it is in the

Maildir format.

OPTIONS

close

Indicate if the user has any mail also on logout.

debug

Print debug information.

dir=maildir

Look for the user's mail in an alternative location defined by maildir/<login>. The default location for mail is /var/mail/<login>. Note, if the supplied maildir is prefixed by a '~', the directory is interpreted as indicating a file in the user's home directory.

empty

Also print message if user has no mail.

hash=count

Mail directory hash depth. For example, a hashcount of 2 would make the mail file be /var/spool/mail/u/s/user.

noenv

Do not set the MAIL environment variable.

nopen

Don't print any mail information on login. This flag is useful to get the MAIL environment variable set, but to not display any information about it.

quiet

Only report when there is new mail.

standard

Old style "You have..." format which doesn't show the mail spool being used. This also implies "empty".

MODULE TYPES PROVIDED

The session and auth (on establishment and deletion of credentials) module types are provided.

RETURN VALUES

PAM_BUF_ERR

Memory buffer error.

PAM_SERVICE_ERR

Badly formed arguments.

PAM_SUCCESS

Success.

PAM_USER_UNKNOWN

User not known.

EXAMPLES

Add the following line to `/etc/pam.d/login` to indicate that the user has new mail when they login to the system.

```
session optional pam_mail.so standard
```

SEE ALSO

`pam.conf(5)`, `pam.d(5)`, `pam(8)`

AUTHOR

`pam_mail` was written by Andrew G. Morgan <morgan@kernel.org>.

