



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'pam\_nologin.8'***

**\$ man pam\_nologin.8**

PAM\_NOLOGIN(8)                  Linux-PAM Manual                  PAM\_NOLOGIN(8)

#### NAME

pam\_nologin - Prevent non-root users from login

#### SYNOPSIS

pam\_nologin.so [file=/path/nologin] [successok]

#### DESCRIPTION

pam\_nologin is a PAM module that prevents users from logging into the system when /var/run/nologin or /etc/nologin exists. The contents of the file are displayed to the user. The pam\_nologin module has no effect on the root user's ability to log in.

#### OPTIONS

file=/path/nologin

Use this file instead the default /var/run/nologin or /etc/nologin.

successok

Return PAM\_SUCCESS if no file exists, the default is PAM\_IGNORE.

#### MODULE TYPES PROVIDED

The auth and account module types are provided.

#### RETURN VALUES

## PAM\_AUTH\_ERR

The user is not root and /etc/nologin exists, so the user is not permitted to log in.

## PAM\_BUF\_ERR

Memory buffer error.

## PAM\_IGNORE

This is the default return value.

## PAM\_SUCCESS

Success: either the user is root or the nologin file does not exist.

## PAM\_USER\_UNKNOWN

User not known to the underlying authentication module.

## EXAMPLES

The suggested usage for /etc/pam.d/login is:

```
auth required pam_nologin.so
```

## NOTES

In order to make this module effective, all login methods should be secured by it. It should be used as a required method listed before any sufficient methods in order to get standard Unix nologin semantics.

Note, the use of successok module argument causes the module to return PAM\_SUCCESS and as such would break such a configuration - failing sufficient modules would lead to a successful login because the nologin module succeeded.

## SEE ALSO

nologin(5), pam.conf(5), pam.d(5), pam(8)

## AUTHOR

pam\_nologin was written by Michael K. Johnson <johnsonm@redhat.com>.