

Full credit is given to the above companies including the OS that this PDF file was generated!

# Rocky Enterprise Linux 9.2 Manual Pages on command 'pam\_stress.8'

## \$ man pam\_stress.8

PAM\_STRESS(8)

Linux-PAM Manual

PAM\_STRESS(8)

NAME

pam stress - The stress-testing PAM module

### **SYNOPSIS**

pam\_stress.so [debug] [no\_warn] [use\_first\_pass] [try\_first\_pass]

[rootok] [expired] [fail\_1] [fail\_2] [prelim] [required]

### **DESCRIPTION**

The pam\_stress PAM module is mainly intended to give the impression of failing as a fully functioning module might.

## **OPTIONS**

#### debug

Put lots of information in syslog. \*NOTE\* this option writes passwords to syslog, so don't use anything sensitive when testing.

### no\_warn

Do not give warnings about things (otherwise warnings are issued via the conversation function)

use\_first\_pass

Do not prompt for a password, for pam\_sm\_authentication function

```
just use item PAM AUTHTOK.
try_first_pass
  Do not prompt for a password unless there has been no previous
  authentication token (item PAM_AUTHTOK is NULL)
rootok
  This is intended for the pam_sm_chauthtok function and it instructs
  this function to permit root to change the user's password without
  entering the old password.
expired
  An argument intended for the account and chauthtok module parts. It
  instructs the module to act as if the user's password has expired
fail_1
  This instructs the module to make its first function fail.
fail 2
  This instructs the module to make its second function (if there is
  one) fail.
prelim
```

For pam\_sm\_chauthtok, means fail if the user hasn't already been

authenticated by this module. (See stress\_new\_pwd data string in

For pam sm chauthtok, means fail on PAM PRELIM CHECK.

the NOTES.)

## MODULE TYPES PROVIDED

All module types (auth, account, password and session) are provided.

# **RETURN VALUES**

required

PAM BUF ERR

Memory buffer error.

PAM\_PERM\_DENIED

Permission denied.

PAM\_AUTH\_ERR

Access to the system was denied.

PAM\_CONV\_ERR

Conversation failure.

```
PAM SUCCESS
      The function passes all checks.
   PAM_USER_UNKNOWN
      The user is not known to the system.
   PAM_CRED_ERR
      Failure involving user credentials.
   PAM_NEW_AUTHTOK_REQD
      Authentication token is no longer valid; new one required.
   PAM SESSION ERR
      Session failure.
   PAM_TRY_AGAIN
      Failed preliminary check by service.
   PAM_AUTHTOK_LOCK_BUSY
      Authentication token lock busy.
   PAM_AUTHTOK_ERR
      Authentication token manipulation error.
   PAM_SYSTEM_ERR
      System error.
NOTES
   This module uses the stress_new_pwd data string which tells
   pam_sm_chauthtok that pam_sm_acct_mgmt says we need a new password. The
   only possible value for this data string is 'yes'.
EXAMPLES
      #%PAM-1.0
      # Any of the following will suffice
      account required pam_stress.so
      auth
             required pam_stress.so
```

# SEE ALSO

pam.conf(5), pam.d(5), pam(8).

password required pam\_stress.so

session required pam\_stress.so

AUTHORS Page 3/4

The pam\_stress PAM module was developed by Andrew Morgan
<morgan@linux.kernel.org>. The man page for pam\_stress was written by
Lucas Ramage <ramage.lucas@protonmail.com>.

Linux-PAM Manual

11/25/2020

PAM\_STRESS(8)