



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pdfimages.1'

\$ man pdfimages.1

pdfimages(1) General Commands Manual pdfimages(1)

NAME

pdfimages - Portable Document Format (PDF) image extractor (version 3.03)

SYNOPSIS

pdfimages [options] PDF-file image-root

DESCRIPTION

Pdfimages saves images from a Portable Document Format (PDF) file as Portable Pixmap (PPM), Portable Bitmap (PBM), Portable Network Graphics (PNG), Tagged Image File Format (TIFF), JPEG, JPEG2000, or JBIG2 files.

Pdfimages reads the PDF file PDF-file, scans one or more pages, and writes one file for each image, image-root-*nnn*.*xxx*, where *nnn* is the image number and *xxx* is the image type (.ppm, .pbm, .png, .tif, .jpg, jp2, jb2e, or jb2g). If PDF-file is ?-', it reads the PDF file from stdin.

The default output format is PBM (for monochrome images) or PPM for non-monochrome. The -png or -tiff options change to default output to PNG or TIFF respectively. If both -png and -tiff are specified, CMYK

images will be written as TIFF and all other images will be written as PNG. In addition the `-j`, `-jp2`, and `-jbig2` options will cause JPEG, JPEG2000, and JBIG2, respectively, images in the PDF file to be written in their native format.

OPTIONS

`-f` number

Specifies the first page to scan.

`-l` number

Specifies the last page to scan.

`-png` Change the default output format to PNG.

`-tiff` Change the default output format to TIFF.

`-j` Write images in JPEG format as JPEG files instead of the default format. The JPEG file is identical to the JPEG data stored in the PDF.

`-jp2` Write images in JPEG2000 format as JP2 files instead of the default format. The JP2 file is identical to the JPEG2000 data stored in the PDF.

`-jbig2` Write images in JBIG2 format as JBIG2 files instead of the default format. JBIG2 data in PDF is of the embedded type. The embedded type of JBIG2 has an optional separate file containing global data. The embedded data is written with the extension `.jb2e` and the global data (if available) will be written to the same image number with the extension `.jb2g`. The content of both these files is identical to the JBIG2 data in the PDF.

`-ccitt` Write images in CCITT format as CCITT files instead of the default format. The CCITT file is identical to the CCITT data stored in the PDF. PDF files contain additional parameters specifying how to decode the CCITT data. These parameters are translated to `fax2tiff` input options and written to a `.params` file with the same image number. The parameters are:

`-1` 1D Group 3 encoding

`-2` 2D Group 3 encoding

`-4` Group 4 encoding

- A Beginning of line is aligned on a byte boundary
- P Beginning of line is not aligned on a byte boundary
- X n The image width in pixels
- W Encoding uses 1 for black and 0 for white
- B Encoding uses 0 for black and 1 for white
- M Input data fills from most significant bit to least significant bit.

-all Write JPEG, JPEG2000, JBIG2, and CCITT images in their native format. CMYK files are written as TIFF files. All other images are written as PNG files. This is equivalent to specifying the options -png -tiff -j -jp2 -jbig2 -ccitt.

-list Instead of writing the images, list the images along with various information for each image. Do not specify an image-root with this option.

The following information is listed for each image:

page the page number containing the image

num the image number

type the image type:

image - an opaque image

mask - a monochrome mask image

smask - a soft-mask image

stencil - a monochrome mask image used for painting a color or pattern

Note: Transparency in images is represented in PDF using a separate image for the image and the mask/smask. The mask/smask used as part of a transparent image always immediately follows the image in the image list.

width image width (in pixels)

height image height (in pixels)

Note: the image width/height is the size of the embedded image, not the size the image will be rendered at.

color image color space:

gray - Gray

rgb - RGB

cmyk - CMYK

lab - L*a*b

icc - ICC Based

index - Indexed Color

sep - Separation

devn - DeviceN

comp number of color components

bpc bits per component

enc encoding:

image - raster image (may be Flate or LZW compressed but does not use an image encoding)

jpeg - Joint Photographic Experts Group

jp2 - JPEG2000

jbig2 - Joint Bi-Level Image Experts Group

ccitt - CCITT Group 3 or Group 4 Fax

interp "yes" if the interpolation is to be performed when scaling up the image

ing up the image

object ID

the image dictionary object ID (number and generation)

x-ppi The horizontal resolution of the image (in pixels per inch) when rendered on the pdf page.

y-ppi The vertical resolution of the image (in pixels per inch) when rendered on the pdf page.

size The size of the embedded image in the pdf file. The following suffixes are used: 'B' bytes, 'K' kilobytes, 'M' megabytes, and 'G' gigabytes.

lowing suffixes are used: 'B' bytes, 'K' kilobytes, 'M'

megabytes, and 'G' gigabytes.

ratio The compression ratio of the embedded image.

-opw password

Specify the owner password for the PDF file. Providing this will bypass all security restrictions.

-upw password

Specify the user password for the PDF file.

- p Include page numbers in output file names.
- q Don't print any messages or errors.
- v Print copyright and version information.
- h Print usage information. (-help and --help are equivalent.)

EXIT CODES

The Xpdf tools use the following exit codes:

- 0 No error.
- 1 Error opening a PDF file.
- 2 Error opening an output file.
- 3 Error related to PDF permissions.
- 99 Other error.

AUTHOR

The pdfimages software and documentation are copyright 1998-2011 Glyph & Cog, LLC.

SEE ALSO

pdfdetach(1), pdffonts(1), pdfinfo(1), pdftocairo(1), pdftohtml(1),
pdftoppm(1), pdftops(1), pdftotext(1) pdfseparate(1), pdfsig(1), pdfu?
nite(1)

15 August 2011

pdfimages(1)