



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pnm2ppa.1'

\$ man pnm2ppa.1

pnm2ppa(28 Oct 2000)

pnm2ppa(28 Oct 2000)

NAME

pnm2ppa - convert portable anymap (PNM) images to HP's PPA printer format.
mat.

SYNOPSIS

pnm2ppa [options] [-i infile] [-o outfile]

DESCRIPTION

Reads portable anymap (PNM) format as input. Binary PNM formats pnmraw = {ppmraw (color pixmap), pgmraw (graymap), and pbmraw (black-and-white bitmap)} are strongly preferred. Output stream can be locally processed by Hewlett-Packard's Printing Performance Architecture (PPA) printers (HP DeskJet 710C, 712C, 720C, 722C, 820C, and 1000C series). (PNM format output can be produced from PostScript(tm) input by the GhostScript output devices "pbmraw", "pgmraw" or "ppmraw", or by "pnm?raw", which will choose one of these formats as appropriate for the document.)

OPTIONS

-b bottommargin

Sets the bottom margin `bottommargin` in units of 1/600 inches (e.g., `-b 150` corresponds to 0.25").

`-B` blackness

Sets the black ink density `blackness` in drops per pixel (0,1,2,3,4).

`--bi` Force bidirectional print sweeps.

`--bw` Disables the color cartridge; will print in grey scale using only the black cartridge.

`-d` Displays the current configuration.

`--eco` Econofast mode: lower print quality that is faster and saves ink.

`-f` `configFile`

Re-reads configuration from `configFile` (after initially reading it from `/etc/pnm2ppa.conf`).

`-F` `GammaFile`

Overrides reading the color-correction table (Gamma curve) from the default file `/etc/pnm2ppa.gamma`, and uses `GammaFile` instead.

`--fd` Enable fast ordered dithering instead of using the slower, but beautiful, Floyd-Steinberg dithering. (Has no effect in `--bw` mode.)

`-g` Prints a page of color intensity samples (for comparison with `gamma.ppm` data produced by `calibrate_ppa`). This is part of a color-correction procedure; see `COLOR.txt` for more details.

`-h, --help`

Displays program usage.

`-i` `infile`

Input file `infile` is either a path to a PPM file, or `'-'` to indicate stdin (defaults to stdin).

`-l` `leftmargin`

Sets the left margin `leftmargin` in units of 1/600 inches (e.g., `-l 150` corresponds to 0.25").

`--noGamma`

Switches off any color-correction.

-o outfile | -

Output file outfile is either a path to a file or device, or '-' to indicate stdout (defaults to stdout).

-p Disables the black ink cartridge; i.e., print using only the color ink cartridge, even for printing "black". This might be useful for printing high-quality color images.

-r rightmargin

Sets the right margin rightmargin in units of 1/600 inches (e.g., -r 150 corresponds to 0.25").

-s papersize

Sets the default paper size (now used only for color-correction output produced by the -g option). In normal use, pnm2ppa now instead reads the paper dimensions from pnm input file headers, and checks that it is a valid papersize for the given printer model. Possible values for papersize are a4 (A4), letter or us (US Letter, 8.5"x11"), legal (US Legal, 8.5"x14"). The default is US Letter.

-t topmargin

Sets the top margin topmargin in units of 1/600 inches (ie -t 150 corresponds to 0.25").

--uni Force unidirectional (left to right) print sweeps. Useful if "shearing" is a problem for high quality color images.

-v printertype

Selects the printer model. Possible values of printertype are: 710, 712, 720, 722, 820 and 1000. The default is the HP DeskJet 7X0 Series (710, 712, 720, 722).

--verbose

Displays the program's System Log messages on the standard output, as well.

--version

Displays the program's version information.

-x xoffset

Sets the x-offset xoffset from the left of the page. Units are

1/600 inches.

-y yoffset

Sets the y-offset yoffset from the top of the page. Units are 1/600 inches.

NOTES

The default configuration file `/etc/pnm2ppa.conf` is read in first.

Command line arguments then modify the resulting definitions.

The `-v` option resets all definitions (margins, offsets, etc.) back to the inbuilt defaults for that printer and should be used before subsequent `-b`, `-l`, `-r`, `-t`, `-x` and `-y` arguments.

SEE ALSO

`pnm(5)`, `ppm(5)`, `pbm(5)`

FILES

`/etc/pnm2ppa.conf`

Default configuration file.

`/etc/pnm2ppa.gamma`

Default Gamma (color-correction) file.

AUTHOR

This code is licensed under the GNU Public License version 2. See LICENSE

for details.

(c) 1998-1999 Tim Norman

(c) 1999 Giorgio Marzano

(c) 1999 Andrew van der Stock

(c) 1998-2000 Various authors for many, many fixes

HISTORY

This program was originally `pbm2ppa`, written by Tim Norman. It originally supported black and white output on the 820 series. Tim added nascent color support in early 1999. In May 1999, Giorgio Marzano started making real headway in getting color support working properly. Andrew van der Stock has maintained the code since September 1999, and made it available at <http://sourceforge.net/projects/pnm2ppa>.

BUGS

Faint horizontal lines marking boundaries between print sweeps may be

visible. For best results when printing images, use the options `-p`
`--uni` .

pnm2ppa(28 Oct 2000)