



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-container-diff.1'

\$ man podman-container-diff.1

podman-container-diff(1) General Commands Manual podman-container-diff(1)

NAME

podman-container-diff - Inspect changes on a container's filesystem

SYNOPSIS

podman container diff [options] container [container]

DESCRIPTION

Displays changes on a container's filesystem. The container will be compared to its parent layer or the second argument when given.

The output is prefixed with the following symbols:

??

?Symbol ? Description ?

??

?A ? A file or directory was added. ?

??

?D ? A file or directory was ?

? ? deleted. ?

??

?C ? A file or directory was ?

? ? changed. ?

??

OPTIONS

`--format`

Alter the output into a different format. The only valid format for podman container diff is json.

`--latest, -l`

Instead of providing the container name or ID, use the last created container. Note: the last started container could be from other users of Podman on the host machine. (This option is not available with the remote Podman client, including Mac and Windows (excluding WSL2) machines)

EXAMPLE

```
# podman container diff container1
C /usr
C /usr/local
C /usr/local/bin
A /usr/local/bin/docker-entrypoint.sh

$ podman container diff --format json container1 container2

{
  "added": [
    "/test"
  ]
}
```

SEE ALSO

podman(1), podman-container(1)

HISTORY

July 2021, Originally compiled by Paul Holzinger pholzinger@redhat.com
?mailto:pholzinger@redhat.com?

podman-container-diff(1)