



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-image-save.1'***

#### ***\$ man podman-image-save.1***

podman-save(1)      General Commands Manual      podman-save(1)

#### NAME

podman-save - Save image(s) to an archive

#### SYNOPSIS

podman save [options] name[:tag]

podman image save [options] name[:tag]

#### DESCRIPTION

podman save saves an image to a local file or directory. podman save writes to STDOUT by default and can be redirected to a file using the output flag. The quiet flag suppresses the output when set. podman save will save parent layers of the image(s) and the image(s) can be loaded using podman load. To export the containers, use the podman export. Note: : is a restricted character and cannot be part of the file name.

podman [GLOBAL OPTIONS]

podman save [GLOBAL OPTIONS]

podman save [OPTIONS] NAME[:TAG]

#### OPTIONS



```
$ podman save > alpine-all.tar alpine
```

```
$ podman save -o oci-alpine.tar --format oci-archive alpine
```

```
$ podman save --compress --format oci-dir -o alp-dir alpine
```

Getting image source signatures

```
Copying blob sha256:2fdfe1cd78c20d05774f0919be19bc1a3e4729bce219968e4188e7e0f1af679d
```

```
1.97 MB / 1.97 MB [=====] 0s
```

```
Copying config sha256:501d1a8f0487e93128df34ea349795bc324d5e0c0d5112e08386a9dfaff620be
```

```
584 B / 584 B [=====] 0s
```

Writing manifest to image destination

Storing signatures

```
$ podman save --format docker-dir -o ubuntu-dir ubuntu
```

Getting image source signatures

```
Copying blob sha256:660c48dd555dcbfdfe19c80a30f557ac57a15f595250e67bfad1e5663c1725bb
```

```
45.55 MB / 45.55 MB [=====] 8s
```

```
Copying blob sha256:4c7380416e7816a5ab1f840482c9c3ca8de58c6f3ee7f95e55ad299abbfe599f
```

```
846 B / 846 B [=====] 0s
```

```
Copying blob sha256:421e436b5f80d876128b74139531693be9b4e59e4f1081c9a3c379c95094e375
```

```
620 B / 620 B [=====] 0s
```

```
Copying blob sha256:e4ce6c3651b3a090bb43688f512f687ea6e3e533132bcbc4a83fb97e7046cea3
```

```
849 B / 849 B [=====] 0s
```

```
Copying blob sha256:be588e74bd348ce48bb7161350f4b9d783c331f37a853a80b0b4abc0a33c569e
```

```
169 B / 169 B [=====] 0s
```

```
Copying config sha256:20c44cd7596ff4807aef84273c99588d22749e2a7e15a7545ac96347baa65eda
```

```
3.53 KB / 3.53 KB [=====] 0s
```

Writing manifest to image destination

Storing signatures

## SEE ALSO

podman(1), podman-load(1), containers.conf(5), containers-transport(5)

## HISTORY

July 2017, Originally compiled by Urvashi Mohnani [umohnani@redhat.com](mailto:umohnani@redhat.com)

[?mailto:umohnani@redhat.com?](mailto:umohnani@redhat.com)

podman-save(1)