



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-pod-pause.1'

\$ man podman-pod-pause.1

podman-pod-pause(1) General Commands Manual podman-pod-pause(1)

NAME

podman-pod-pause - Pause one or more pods

SYNOPSIS

podman pod pause [options] pod ...

DESCRIPTION

Pauses all the running processes in the containers of one or more pods.

You may use pod IDs or names as input.

OPTIONS

--all, -a

Pause all pods.

--latest, -l

Instead of providing the pod name or ID, pause the last created pod.

(This option is not available with the remote Podman client, including

Mac and Windows (excluding WSL2) machines)

EXAMPLE

Pause a pod with a given name

```
podman pod pause mywebserverpod
```

Pause a pod with a given ID

```
podman pod pause 860a4b23
```

SEE ALSO

[podman\(1\)](#), [podman-pod\(1\)](#), [podman-pod-unpause\(1\)](#), [podman-pause\(1\)](#)

HISTORY

July 2018, Originally compiled by Peter Hunt pehunt@redhat.com

[?mailto:pehunt@redhat.com?](mailto:pehunt@redhat.com)

[podman-pod-pause\(1\)](#)