



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-system-prune.1'

\$ man podman-system-prune.1

podman-system-prune(1) General Commands Manual podman-system-prune(1)

NAME

podman-system-prune - Remove all unused pods, containers, images, networks, and volume data

SYNOPSIS

podman system prune [options]

DESCRIPTION

podman system prune removes all unused containers (both dangling and unreferenced), pods, networks, and optionally, volumes from local storage.

Use the --all option to delete all unused images. Unused images are dangling images as well as any image that does not have any containers based on it.

By default, volumes are not removed to prevent important data from being deleted if there is currently no container using the volume. Use the --volumes flag when running the command to prune volumes as well.

OPTIONS

--all, -a

Recursively remove all unused pods, containers, images, networks, and volume data. (Maximum 50 iterations.)

`--external`

Removes all leftover container storage files from local storage that are not managed by podman. In normal circumstances no such data should exist, but in case of an unclean shutdown the podman database may be corrupted and cause his.

However, when using transient storage mode, the Podman database does not persist. This means containers will leave the writable layers on disk after a reboot. When using a transient store, it is recommended that the podman system prune `--external` command is run during boot.

This option is incompatible with `--all` and `--filter` and drops the default behaviour of removing unused resources.

`--filter=filters`

Provide filter values.

The filters argument format is of `key=value`. If there is more than one filter, then pass multiple OPTIONS: `--filter foo=bar --filter bif=baz`.

Supported filters:

??

?Filter ? Description ?

??

?label ? Only remove containers and ?

? ? images, with (or without, ?

? ? in the case of la? ?

? ? bell!=[...] is used) the ?

? ? specified labels. ?

??

?until ? Only remove containers and ?

? ? images created before ?

? ? given timestamp. ?

??

The label filter accepts two formats. One is the `label=key` or `la?`

`bel=key=value`, which removes containers and images with the specified

labels. The other format is the label!=key or label!=key=value, which removes containers and images without the specified labels.

The until filter can be Unix timestamps, date formatted timestamps, or Go duration strings (e.g. 10m, 1h30m) computed relative to the machine's time.

--force, -f

Do not prompt for confirmation

--help, -h

Print usage statement

--volumes

Prune volumes currently unused by any container

SEE ALSO

podman(1), podman-system(1)

HISTORY

February 2019, Originally compiled by Dan Walsh (dwalsh at redhat dot com) December 2020, converted filter information from docs.docker.com documentation by Dan Walsh (dwalsh at redhat dot com)

podman-system-prune(1)