



Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-volume-prune.1'

\$ man podman-volume-prune.1

podman-volume-prune(1) General Commands Manual podman-volume-prune(1)

NAME

podman-volume-prune - Remove all unused volumes

SYNOPSIS

podman volume prune [options]

DESCRIPTION

Removes unused volumes. By default all unused volumes will be removed, the --filter flag can be used to filter specific volumes. You will be prompted to confirm the removal of all the unused volumes. To bypass the confirmation, use the --force flag.

OPTIONS

--filter

Provide filter values.

The filters argument format is of key=value. If there is more than one filter, then pass multiple OPTIONS: --filter foo=bar --filter bif=baz.

Supported filters:

??

?Filter ? Description ?

??

?label ? Only remove volumes, with ?

? ? (or without, in the case ?

? ? of label!=[...] is used) ?

? ? the specified labels. ?

??

?until ? Only remove volumes cre? ?

? ? ated before given time? ?

? ? stamp. ?

??

The label filter accepts two formats. One is the label=key or la?
bel=key=value, which removes volumes with the specified labels. The
other format is the label!=key or label!=key=value, which removes vol?
umes without the specified labels.

The until filter can be Unix timestamps, date formatted timestamps, or
Go duration strings (e.g. 10m, 1h30m) computed relative to the ma?
chine?s time.

--force, -f

Do not prompt for confirmation.

--help

Print usage statement

EXAMPLES

\$ podman volume prune

\$ podman volume prune --force

\$ podman volume prune --filter label=mylabel=mylabelvalue

SEE ALSO

podman(1), podman-volume(1)

HISTORY

November 2018, Originally compiled by Urvashi Mohnani umohnani@red?
hat.com ?mailto:umohnani@redhat.com?

podman-volume-prune(1)