



*Full credit is given to the above companies including the OS that this PDF file was generated!*

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'rasdaemon.1'***

***\$ man rasdaemon.1***

RASDAEMON(8)      RAS memory controller admin utility      RASDAEMON(8)

#### NAME

rasdaemon - RAS daemon to log the RAS events.

#### SYNOPSIS

rasdaemon [OPTION]...

#### DESCRIPTION

The rasdaemon program is a daemon which monitors the platform Reliability, Availability and Serviceability (RAS) reports from the Linux kernel trace events. These trace events are logged in /sys/kernel/debug/tracing, reporting them via syslog/journald.

#### OPTIONS

--usage

Display a brief usage message and exit.

--help Display a help message and exit.

--disable

Disable RAS tracing events and exit.

--enable

Enable RAS tracing events and exit.

--foreground

Executes in foreground, printing the events at console. Useful for testing it, and to be used by systemd or Unix System V respawn. If not specified, the program runs in daemon mode.

--record

Record RAS events via SQLite3. The SQLite3 database has the benefit of keeping a persistent record of the RAS events. This feature is used with the ras-mc-ctl utility. Note that rasdaemon may be compiled without this feature.

--version

Print the program version and exit.

## CONFIG FILE

The rasdaemon program supports a config file to set rasdaemon systemd service environment variables. By default the config file is read from /etc/sysconfig/rasdaemon.

The general format is environmentname=value.

## SEE ALSO

ras-mc-ctl(8)

RASDAEMON(8)