



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'repertoiremap.5'

\$ man repertoiremap.5

REPertoireMAP(5) Linux User Manual REPertoireMAP(5)

NAME

repertoiremap - map symbolic character names to Unicode code points

DESCRIPTION

A repertoire map defines mappings between symbolic character names (mnemonics) and Unicode code points when compiling a locale with `localedef(1)`. Using a repertoire map is optional, it is needed only when symbolic names are used instead of now preferred Unicode code points.

Syntax

The repertoiremap file starts with a header that may consist of the following keywords:

comment_char

is followed by a character that will be used as the comment character for the rest of the file. It defaults to the number sign (#).

escape_char

is followed by a character that should be used as the escape character for the rest of the file to mark characters that

should be interpreted in a special way. It defaults to the
backslash (\).

The mapping section starts with the keyword CHARIDS in the first column.

The mapping lines have the following form:

```
<symbolic-name> <code-point> comment
```

This defines exactly one mapping, comment being optional.

The mapping section ends with the string END CHARIDS.

FILES

```
/usr/share/i18n/repertoiremaps
```

Usual default repertoire map path.

CONFORMING TO

POSIX.2.

NOTES

Repertoire maps are deprecated in favor of Unicode code points.

EXAMPLES

A mnemonic for the Euro sign can be defined as follows:

```
<Eu> <U20AC> EURO SIGN
```

SEE ALSO

locale(1), localedef(1), charmap(5), locale(5)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.