



*Full credit is given to the above companies including the OS that this PDF file was generated!*

**ky Enterprise Linux 9.2 Manual Pages on command 'rmiregistry-java-20-openjdk-20.0.2.0.9-1.rolling.el9.x86\_**

**\$ man rmiregistry-java-20-openjdk-20.0.2.0.9-1.rolling.el9.x86\_64.1**

RMIREGISTRY(1)                   JDK Commands                   RMIREGISTRY(1)

NAME

rmiregistry - create and start a remote object registry on the specified port on the current host

SYNOPSIS

rmiregistry [options] [port]

options

This represents the option for the rmiregistry command. See Options

port The number of a port on the current host at which to start the remote object registry.

DESCRIPTION

The rmiregistry command creates and starts a remote object registry on the specified port on the current host. If the port is omitted, then the registry is started on port 1099. The rmiregistry command produces no output and is typically run in the background, for example:

rmiregistry &

A remote object registry is a bootstrap naming service that's used by

RMI servers on the same host to bind remote objects to names. Clients on local and remote hosts can then look up remote objects and make remote method invocations.

The registry is typically used to locate the first remote object on which an application needs to call methods. That object then provides application-specific support for finding other objects.

The methods of the `java.rmi.registry.LocateRegistry` class are used to get a registry operating on the local host or local host and port.

The URL-based methods of the `java.rmi.Naming` class operate on a registry and can be used to:

- ? Bind the specified name to a remote object
- ? Return an array of the names bound in the registry
- ? Return a reference, a stub, for the remote object associated with the specified name
- ? Rebind the specified name to a new remote object
- ? Destroy the binding for the specified name that's associated with a remote object

## OPTIONS

-Joption

Used with any Java option to pass the option following the -J (no spaces between the -J and the option) to the Java interpreter.

JDK 20

2023

RMIREGISTRY(1)