



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'rpc.5'

\$ man rpc.5

RPC(5) Linux Programmer's Manual RPC(5)

NAME

rpc - RPC program number data base

SYNOPSIS

/etc/rpc

DESCRIPTION

The rpc file contains user readable names that can be used in place of RPC program numbers. Each line has the following information:

- ? name of server for the RPC program
- ? RPC program number
- ? aliases

Items are separated by any number of blanks and/or tab characters. A '#' indicates the beginning of a comment; characters from the '#' to the end of the line are not interpreted by routines which search the file.

Here is an example of the /etc/rpc file from the Sun RPC Source distribution.

#

rpc 88/08/01 4.0 RPCSRC; from 1.12 88/02/07 SMI

#

portmapper 100000 portmap sunrpc
rstatd 100001 rstat rstat_svc rup perfmeter
rusersd 100002 rusers
nfs 100003 nfsprog
ypserv 100004 ypprog
mountd 100005 mount showmount
ypbind 100007
walld 100008 rwall shutdown
yppasswdd 100009 yppasswd
etherstatd 100010 etherstat
rquotad 100011 rquotaprog quota rquota
sprayd 100012 spray
3270_mapper 100013
rje_mapper 100014
selection_svc 100015 selnsvc
database_svc 100016
rexd 100017 rex
alis 100018
sched 100019
llockmgr 100020
nlockmgr 100021
x25.inr 100022
statmon 100023
status 100024
bootparam 100026
ypupdated 100028 ypupdate
keyserv 100029 keyserver
tfsd 100037
nsed 100038
nsemntd 100039

/etc/rpc

RPC program number data base

SEE ALSO

getrpcent(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

RPC(5)