



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'saslpaswd2.8'

\$ man saslpaswd2.8

SASLPASSWD2(8) System Manager's Manual SASLPASSWD2(8)

NAME

saslpaswd2 - set a user's sasl password

SYNOPSIS

saslpaswd2 [-p] [-d] [-c] [-n] [-f file] [-u domain] [-a appname] [-v]
userid

DESCRIPTION

saslpaswd2 is used by a server administrator to set a user's sasl password for server programs and SASL mechanisms which use the standard libsasl database of user secrets.

OPTIONS

-p Pipe mode - saslpaswd2 will neither prompt for the password nor verify that it was entered correctly. This is the default when

standard input is not a terminal.

- c Creates an entry for the user if the user doesn't already exist.
This is mutually exclusive with the -d (delete user) flag.

- d Deletes the entry for the user. This is mutually exclusive with
the -c (create user) flag.

- n Don't set the plaintext userPassword property for the user.
Only mechanism-specific secrets will be set (e.g. OTP, SRP)

- u domain
use domain for user domain (realm).

- f file
use file for sasldb

- a appname
use appname as application name.

- v Print libsasl2 version number and exit.

SEE ALSO

[sasldblistusers2\(8\)](#)

[rfc4422 - Simple Authentication and Security Layer \(SASL\)](#)