



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sched_getattr.2'

\$ man sched_getattr.2

SCHED_SETATTR(2) Linux Programmer's Manual SCHED_SETATTR(2)

NAME

 sched_setattr, sched_getattr - set and get scheduling policy and at?

 tributes

SYNOPSIS

```
#include <sched.h>
```

```
int sched_setattr(pid_t pid, struct sched_attr *attr,  
                  unsigned int flags);
```

```
int sched_getattr(pid_t pid, struct sched_attr *attr,  
                  unsigned int size, unsigned int flags);
```

DESCRIPTION

 sched_setattr()

 The sched_setattr() system call sets the scheduling policy and associated attributes for the thread whose ID is specified in pid. If pid equals zero, the scheduling policy and attributes of the calling thread will be set.

 Currently, Linux supports the following "normal" (i.e., non-real-time) scheduling policies as values that may be specified in policy:

SCHED_OTHER the standard round-robin time-sharing policy;

SCHED_BATCH for "batch" style execution of processes; and

SCHED_IDLE for running very low priority background jobs.

Various "real-time" policies are also supported, for special time-crit?

ical applications that need precise control over the way in which

runnable threads are selected for execution. For the rules governing

when a process may use these policies, see sched(7). The real-time

policies that may be specified in policy are:

SCHED_FIFO a first-in, first-out policy; and

SCHED_RR a round-robin policy.

Linux also provides the following policy:

SCHED_DEADLINE

a deadline scheduling policy; see sched(7) for details.

The attr argument is a pointer to a structure that defines the new

scheduling policy and attributes for the specified thread. This struc?

ture has the following form:

```
struct sched_attr {
    u32 size;          /* Size of this structure */
    u32 sched_policy;  /* Policy (SCHED_*) */
    u64 sched_flags;   /* Flags */
    s32 sched_nice;    /* Nice value (SCHED_OTHER,
                       SCHED_BATCH) */
    u32 sched_priority; /* Static priority (SCHED_FIFO,
                       SCHED_RR) */
    /* Remaining fields are for SCHED_DEADLINE */
    u64 sched_runtime;
    u64 sched_deadline;
    u64 sched_period;
};
```

The fields of the sched_attr structure are as follows:

size This field should be set to the size of the structure in bytes,

as in sizeof(struct sched_attr). If the provided structure is

smaller than the kernel structure, any additional fields are as?

sumed to be '0'. If the provided structure is larger than the kernel structure, the kernel verifies that all additional fields are 0; if they are not, sched_setattr() fails with the error E2BIG and updates size to contain the size of the kernel structure.

The above behavior when the size of the user-space sched_attr structure does not match the size of the kernel structure allows for future extensibility of the interface. Malformed applications that pass oversized structures won't break in the future if the size of the kernel sched_attr structure is increased. In the future, it could also allow applications that know about a larger user-space sched_attr structure to determine whether they are running on an older kernel that does not support the larger structure.

sched_policy

This field specifies the scheduling policy, as one of the SCHED_* values listed above.

sched_flags

This field contains zero or more of the following flags that are ORed together to control scheduling behavior:

SCHED_FLAG_RESET_ON_FORK

Children created by fork(2) do not inherit privileged scheduling policies. See sched(7) for details.

SCHED_FLAG_RECLAIM (since Linux 4.13)

This flag allows a SCHED_DEADLINE thread to reclaim bandwidth unused by other real-time threads.

SCHED_FLAG_DL_OVERRUN (since Linux 4.16)

This flag allows an application to get informed about run-time overruns in SCHED_DEADLINE threads. Such overruns may be caused by (for example) coarse execution time accounting or incorrect parameter assignment. Notification takes the form of a SIGXCPU signal which is generated on each overrun.

This SIGXCPU signal is process-directed (see `signal(7)`) rather than thread-directed. This is probably a bug. On the one hand, `sched_setattr()` is being used to set a per-thread attribute. On the other hand, if the process-directed signal is delivered to a thread inside the process other than the one that had a run-time overrun, the application has no way of knowing which thread overran.

`sched_nice`

This field specifies the nice value to be set when specifying `sched_policy` as `SCHED_OTHER` or `SCHED_BATCH`. The nice value is a number in the range -20 (high priority) to +19 (low priority); see `sched(7)`.

`sched_priority`

This field specifies the static priority to be set when specifying `sched_policy` as `SCHED_FIFO` or `SCHED_RR`. The allowed range of priorities for these policies can be determined using `sched_get_priority_min(2)` and `sched_get_priority_max(2)`. For other policies, this field must be specified as 0.

`sched_runtime`

This field specifies the "Runtime" parameter for deadline scheduling. The value is expressed in nanoseconds. This field, and the next two fields, are used only for `SCHED_DEADLINE` scheduling; for further details, see `sched(7)`.

`sched_deadline`

This field specifies the "Deadline" parameter for deadline scheduling. The value is expressed in nanoseconds.

`sched_period`

This field specifies the "Period" parameter for deadline scheduling. The value is expressed in nanoseconds.

The `flags` argument is provided to allow for future extensions to the interface; in the current implementation it must be specified as 0.

`sched_getattr()`

The `sched_getattr()` system call fetches the scheduling policy and the

associated attributes for the thread whose ID is specified in `pid`. If `pid` equals zero, the scheduling policy and attributes of the calling thread will be retrieved.

The `size` argument should be set to the size of the `sched_attr` structure as known to user space. The value must be at least as large as the size of the initially published `sched_attr` structure, or the call fails with the error `EINVAL`.

The retrieved scheduling attributes are placed in the fields of the `sched_attr` structure pointed to by `attr`. The kernel sets `attr.size` to the size of its `sched_attr` structure.

If the caller-provided `attr` buffer is larger than the kernel's `sched_attr` structure, the additional bytes in the user-space structure are not touched. If the caller-provided structure is smaller than the kernel `sched_attr` structure, the kernel will silently not return any values which would be stored outside the provided space. As with `sched_setattr()`, these semantics allow for future extensibility of the interface.

The `flags` argument is provided to allow for future extensions to the interface; in the current implementation it must be specified as 0.

RETURN VALUE

On success, `sched_setattr()` and `sched_getattr()` return 0. On error, -1 is returned, and `errno` is set to indicate the cause of the error.

ERRORS

`sched_getattr()` and `sched_setattr()` can both fail for the following reasons:

`EINVAL` `attr` is `NULL`; or `pid` is negative; or `flags` is not zero.

`ESRCH` The thread whose ID is `pid` could not be found.

In addition, `sched_getattr()` can fail for the following reasons:

`E2BIG` The buffer specified by `size` and `attr` is too small.

`EINVAL` `size` is invalid; that is, it is smaller than the initial version of the `sched_attr` structure (48 bytes) or larger than the system page size.

In addition, `sched_setattr()` can fail for the following reasons:

E2BIG The buffer specified by `size` and `attr` is larger than the kernel structure, and one or more of the excess bytes is nonzero.

EBUSY `SCHED_DEADLINE` admission control failure, see `sched(7)`.

EINVAL `attr.sched_policy` is not one of the recognized policies; `attr.sched_flags` contains a flag other than `SCHED_FLAG_RE?` `SET_ON_FORK`; or `attr.sched_priority` is invalid; or `attr.sched_policy` is `SCHED_DEADLINE` and the deadline scheduling parameters in `attr` are invalid.

EPERM The caller does not have appropriate privileges.

EPERM The CPU affinity mask of the thread specified by `pid` does not include all CPUs in the system (see `sched_setaffinity(2)`).

VERSIONS

These system calls first appeared in Linux 3.14.

CONFORMING TO

These system calls are nonstandard Linux extensions.

NOTES

`sched_setattr()` provides a superset of the functionality of `sched_setscheduler(2)`, `sched_setparam(2)`, `nice(2)`, and (other than the ability to set the priority of all processes belonging to a specified user or all processes in a specified group) `setpriority(2)`. Analogously, `sched_getattr()` provides a superset of the functionality of `sched_getscheduler(2)`, `sched_getparam(2)`, and (partially) `getpriority(2)`.

BUGS

In Linux versions up to 3.15, `sched_setattr()` failed with the error `EFAULT` instead of `E2BIG` for the case described in **ERRORS**.

In Linux versions up to 5.3, `sched_getattr()` failed with the error `E2BIG` if the in-kernel `sched_attr` structure was larger than the size passed by user space.

SEE ALSO

`chrt(1)`, `nice(2)`, `sched_get_priority_max(2)`, `sched_get_priority_min(2)`, `sched_getaffinity(2)`, `sched_getparam(2)`, `sched_getscheduler(2)`, `sched_rr_get_interval(2)`, `sched_setaffinity(2)`, `sched_setparam(2)`,

sched_setscheduler(2), sched_yield(2), setpriority(2),
pthread_getschedparam(3), pthread_setschedparam(3),
pthread_setschedprio(3), capabilities(7), cpuset(7), sched(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux 2020-11-01 SCHED_SETATTR(2)