

Do not reload policy after commit

-S STORE, --store STORE

Select an alternate SELinux Policy Store to manage

-C, --locallist

List local customizations

-a, --add

Add a record of the specified object type

-d, --delete

Delete a record of the specified object type

-m, --modify

Modify a record of the specified object type

-l, --list

List records of the specified object type

-E, --extract

Extract customizable commands, for use within a transaction

-D, --deleteall

Remove all local customizations

-L LEVEL, --level LEVEL

Default SELinux Level for SELinux user, s0 Default. (MLS/MCS Systems only)

-r RANGE, --range RANGE

MLS/MCS Security Range (MLS/MCS Systems only) SELinux Range for SELinux login mapping defaults to the SELinux user record range.

SELinux Range for SELinux user defaults to s0.

-R [ROLES], --roles [ROLES]

SELinux Roles. You must enclose multiple roles within quotes, separate by spaces. Or specify -R multiple times.

EXAMPLE

List SELinux users

```
# semanage user -l
```

Modify groups for staff_u user

```
# semanage user -m -R "system_r unconfined_r staff_r" staff_u
```

Add level for TopSecret Users

```
# semanage user -a -R "staff_r" -rs0-TopSecret topsecret_u
```

SEE ALSO

selinux(8), semanage(8), semanage-login(8)

AUTHOR

This man page was written by Daniel Walsh <dwalsh@redhat.com>

20130617

semanage-user(8)