



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'setregdomain.1'

\$ man setregdomain.1

setregdomain(1) User Commands setregdomain(1)

NAME

setregdomain - set regulatory domain based on country code

SYNOPSIS

setregdomain

DESCRIPTION

setregdomain sets the regulatory domain for your system; it takes no arguments and is normally called via system script (eg, udev) rather than manually by an administrator.

The regulatory domain is represented by an ISO / IEC 3166-1 alpha2 country code. By default, setregdomain attempts to determine the appropriate country code by examining the target of the /etc/localtime symbolic link. That information is used to look-up the matching country code in the /usr/share/zoneinfo/zone.tab file.

The country code look-up may fail. This could be due to faulty or incomplete information in the /usr/share/zoneinfo/zone.tab file, or the use of an actual file rather than a symlink for /etc/localtime, among other possibilities. In those cases the system administrator should

define a COUNTRY environment variable in the /etc/sysconfig/regdomain file. This value will be used as the country code and the country code look-up will be skipped.

FILES

/etc/sysconfig/regdomain /etc/localtime /usr/share/zoneinfo/zone.tab

SEE ALSO

iw(1)

CRDA 2014-11-19 segregdomain(1)