



Full credit is given to the above companies including the OS that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'setroubleshootd.8'

\$ man setroubleshootd.8

setroubleshootd(8) setroubleshootd(8)

NAME

setroubleshootd - setroubleshoot daemon

SYNOPSIS

setroubleshootd [-d] [-f] [-h] [-c config]

DESCRIPTION

This manual page describes the setroubleshootd program.

setroubleshootd is the dbus service in the setroubleshoot system.

setroubleshoot is used to diagnose SELinux denials and attempts to provide

user friendly explanations for a SELinux denial (e.g. AVC) and

recommendations for how one might adjust the system to prevent the denial

in the future.

In a standard configuration setroubleshoot is composed of two components,

sealert and setroubleshootd.

setroubleshootd is a system daemon which runs under setroubleshoot user

and listens for audit events emitted from the kernel related to

SELinux. When the setroubleshootd daemon sees an SELinux AVC denial it

runs a series of analysis plugins which examine the audit data related

to the AVC. It records the results of the analysis and signals any clients which have attached to the setroubleshootd daemon that a new alert has been seen.

setroubleshootd is not persistent and only runs when there are new AVCs to be analyzed. It is executed using setroubleshootd.service, which also limits its priority and maximum RAM utilization to 1GB, in order to help with system responsiveness in case of large amounts of AVCs.

OPTIONS

-f --nofork

Do not fork the daemon

-d --debug

Do not exit after 10 seconds of inactivity

-h --help

Show this message

-c --config

section.option=value set a configuration value

AUTHOR

This man page was written by Dan Walsh <dwalsh@redhat.com>.

SEE ALSO

sealert(8),selinux(8)

20100520

setroubleshootd(8)